

B.



Gambit

Extended Specifications

Application	Heavy Commercial
Total Thickness	2mm and 2.5mm option
Total Mass	2mm: $\pm 4.5\text{kg/m}^2$ 2.5mm: $\pm 5.4\text{kg/m}^2$
Standard Size	30cm x 30cm
Quantity Per Box	50 tiles per box (4.5m ²)
Fire Index	1 (SANS 10177-4)
Indentation	Pass (Suitable for intensive use) (SANS 581)
Residual Indentation	Pass (Excellent recovery from indentation) (SANS 581)
Chemical Resistance	Good resistance to everyday substances. Advice is available on resistance to specific chemicals and dilution.
Static Electrical Charge	Classified as electrically insulating. Not conductive or anti-static in nature.
Underfloor Heating	Suitable provided that the temperature of the surface of the sub-floor does not exceed 27°C.
VOC Emissions – Green Building Specifications	0.01 $\mu\text{g}/\text{m}^2/\text{hour}$

B.

Gambit




Burly Blue | 2mm




Brute Force | 2 & 2.5mm



Cast Iron | 2mm



Endure Green | 2mm



Hard Lead | 2 & 2.5mm



Ox Brawn | 2 & 2.5mm



Sand Storm | 2mm



Solid Steel | 2 & 2.5mm

Gambit

Heavy Commercial:
Vinyl Tile



Staircase
Suitable

Medium/General
Commercial

Heavy
Commercial

From Local &
Imported Goods

SABS
ISO 9001

SABS
ISO 14001

Bill of Quantities

- Supply and fix 2.0mm/2.5mm thick x 300mm x 300mm Gambit semi-flexible vinyl tiles manufactured in accordance with SANS 581 on prepared Class 1 sub floor in accordance with the SANS 10070. The newly laid floor must, after 72 hours, be stripped and sealed.
- Belgotex Gambit tile to be installed in tessellated format only.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd.
© BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.