B_

Davenport

Davenport is a combination of rustic tones and textures, which makes it the perfect product for any commercial installation that requires performance as well as aesthetic appeal. These latest colour and texture trends are not just for "show", they are backed up by a 0,55mm wear layer which means it will perform in heavy commercial areas as well as look great in any trendy home.

Extended Specifications

Use Classification: Heavy Commercial Type of Installation: Dry Back (Stick Down)

Overall Thickness: 3mm
Wear Layer Thickness: 0.55mm

Plank Size: 1219.2mm x 184.15mm (l x w)

SQM Per Box: 3.37sqm
Quantity of Planks Per Box: 15
VOC Tested: Passed
Quantity Per Box: 3.37m2

Number of Planks: 15 Planks Per Box
Abrasion Resistance: Group T (EN 660)
Fire Resistance: Bfl-s1 (EN 13501-1)
Stain & Chemical Resistance: Excellent (EN 423)
Slip Resistance: > 0.3 (EN 13893)

Castor Chair: Pass (EN 425)(Use soft non-staining wheels)





Mockernut



Peanut






Macadamia Nut











Pekea Nut

Soybean

Davenport



Heating





Commercial















Bill of Quantities

- Belgotex Davenport 3mm heavy commercial dryback stick down LVT.
- 1219.2mm x 184.15mm (l x w) with 0.55 mm wear layer.
- 20-year residential warranty and 10-year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.