# Penninsula

As leaders of change in the flooring industry, Belgotex knows how important it is to create new products inspired by nature, that help you improve your life. That's why we've introduced Penninsula, an innovative vinyl product that is perfect for any contemporary setting.

### **Extended Specifications**

**Heavy Commercial** Use Classification: Type of Installation: Dry Back (Stick Down)

Overall Thickness: 2.5mm Wear Layer Thickness: 0.55mm

Plank Size: 1516.9mm x 228.6mm (l x w)

Passed

SQM Per Box: 3.47sqm Quantity of Planks Per Box:

**VOC Tested:** 

Certification: Global GreenTag

**Quantity Per Box:** 3.47m2

Number of planks: 10 planks per box Stain & Chemical Resistance: YES (EN 26987)

Slip Resistance: Residual Indentation: Thermal Conductivity: Thermal Resistance: Dimensional Stability: Colour Fastness:

Sound Absorption:

Castor Chair:

Fire Index:

Bfl-s1 (EN13501) wheels)

DS-R10 (DIN 51130) < 0.1mm (EN 24343-1) 0.091 (W/m\*K) 0.028 (m2K) / W (EN 12664) Electrostatic Behaviour: 0.1 kV (EN 1815 Method A) ≤0.25% (EN ISO 2399) > 6 Grade (ISO 105-B02) Approx. 3dB (EN 10140) Yes, Type W (EN ISO 4918) (Use soft non-staining





## Penninsula



Heating























### **Bill of Quantities**

- Belgotex Penninsula 2.5mm heavy commercial dry back stick down LVT.
- 1516.9mm x 228.6mm (l x w) with 0.55 mm wear layer.
- 20-year residential warranty and 10-year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.