

B.

# Sylvan

There is a strong relationship between the properties of wood and the tree that yielded it. These 8 colours all bear the mythical beauty of the forest – minus the cost to nature and your pocket. Delivering comfort and elegance to every room in your home need not be a fairy tale, because you deserve to live happily ever after.

## Extended Specifications

Use Classification:	Heavy Commercial	Fire Index:	Bfl-s1 (EN13501)
Type of Installation:	Dry Back (Stick Down)	Slip Resistance:	DS-R10 (DIN 51130)
Overall Thickness:	2.5mm	Residual Indentation:	< 0.1mm (EN 24343)
Wear Layer Thickness:	0.55mm	Thermal Conductivity:	0.091 W/m*K (EN 12664)
Tile Size:	1219.2mm x 177.8mm (l x w)	Electrostatic Behaviour:	0.1 kV (EN 1815)
VOC Tested:	Passed	Dimensional Stability:	≤0.25% (EN ISO 23999)
Certification:	Global GreenTag	Colour Fastness:	> 6 Grade (ISO 105-B02)
Quantity Per Box:	3.25m2	Sound Absorption:	Approx. 3dB (EN 10140)
Number of tiles:	15 tiles per box	Castor Chair:	Yes, Type W (EN 4918) (Use soft non-staining wheels)
Chemical Resistance:	YES (EN 26987)		





B.



Cedar



Fir



Larch



Pine



Redwood



Spruce



Whitewood



Yew

# Sylvan



### Bill of Quantities

- Belgotex Sylvan 2.5mm heavy commercial dry back stick down LVT.
- 1219.2mm x 177.8mm (l x w) with 0.55 mm wear layer.
- 20-year residential warranty and 10 year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- Green tag level A Gold rated certification.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.