

END-TO-END POWER CHAIR SOLUTIONS



	JAZZY [®] AIR [®] 2 ¹	JAZZY [®] PASSPORT ¹	GO CHAIR [®] 1 ¹	JAZZY [®] EVO 613 SERIES ¹	GO CHAIR [®] MED ¹	JAZZY [®] ELITE ES ¹	JAZZY [®] SELECT ¹	JAZZY [®] ELITE 14 ¹	JAZZY [®] 600 ES ¹	JAZZY [®] ELITE HD ¹	JAZZY [®] 614 HD ¹	JAZZY [®] 1450 ¹
Weight Capacity	300 lbs.	250 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	450 lbs. ⁷	450 lbs.	600 lbs.
Turning Radius ¹¹	24.25"	24.25"	25.5"	22"	25.5"	24.75"	22.5"	24"	20.5"	24"	22.75"	26.5"
Width ¹¹	23.25"	23.5"	22.5"	22"	23"	22.75"	22.75"	24.25"	24.5"	24.25"	25.125"	29.25"
Length ^{11,2}	33.21"/42" (with footplate)	40" (with footplate)	28.5"/33" (with footplate)	35"	28.5"/33" (with footplate)	34.75"/41" (with footplate)	32.99"/44" (with footplate)	35.5"/42.5" (with footplate)	35.5"/40.25" (with footplate)	35.5"	35.5"/40" (with footplate)	38.25"
Maximum Speed ³	Up to 4 mph (elevated and non-elevated)	Up to 3.6 mph	Up to 3.8 mph	Up to 5.1 mph	Up to 3.7 mph	Up to 4 mph	Up to 4.3 mph	Up to 4 mph	Up to 4 mph	Up to 4 mph	Up to 4.25 mph	Up to 4.9 mph
Ground Clearance ¹¹	1" at motor bracket	3" at motor	1.75" at motor	3" at motor bracket	1.75" at motor	1.85" at motors	.75" at motor bracket	3" at battery tray	2.75"	3"	2.25"	1.5" at anti-tips
Front Wheels	6" solid casters	8" solid casters	6" solid casters	5" solid	6" solid casters	3" solid anti-tips	5" solid anti-tips	3" solid anti-tips	6" solid OMNI-casters	3" solid anti-tips	6" solid casters	4" solid anti-tips
Drive Wheels	10" solid	11.25" perforated	9" solid	13" solid	9" solid	9" solid	10" solid	14" foam filled	14" foam filled	14" foam filled	14" foam filled	14" solid
Rear Wheels	6" solid casters	1.75" anti-tips	3" solid anti-tips	5" solid	3" solid anti-tips	6" solid casters	6" solid casters	6" solid casters	6" solid OMNI-casters	6" solid casters	6" solid casters	9" solid casters
Drivetrain	Two-motor, Mid-Wheel 6 [®] drive	Two-motor, rear-wheel drive	Two-motor, rear-wheel drive	Two-motor, in-line, front-wheel drive	Two-motor, rear-wheel drive	Two-motor, in-line, front-wheel drive	Two-motor, mid-wheel drive	Two-motor, front-wheel drive	Two-motor, mid-wheel drive	Two-motor, front-wheel drive	Two-motor, Mid-Wheel 6 [®] drive	Two-motor, front-wheel drive
Braking System	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical
Suspension Type	Active-Trac [®] (ATX) with Mid-Wheel 6 [®] Technology	Limited	Limited	Active-Trac [®] (ATX)	Limited	Limited	Active-Trac [®] (ATX)	Limited	Active-Trac [®] (ATX) with Mid-wheel 6 [®] technology	Limited	Active-Trac [®] with Mid-wheel 6 [®] technology	Swing Arm
High-Back Seat (max. size)	20"W x 20-22"D	N/A	N/A	20"W x 18-20"D	N/A	20"W x 20"D	20"W x 20"D	22"W x 22"D	20"W x 20"D	22"W x 22"D	24"W x 24"D	32"W x 28"D
High-Back Seat-to-Floor Range	21.25-33"	19"	N/A	19.75-21.25"	N/A	21.5-23.5"	21-22"	20-22"	20.5-22.5"	20-22"	20.5-23.5"	20.5-22.5"
Synergy [®] Seating	N/A	N/A	N/A	N/A	N/A	N/A	20"W x 20"D	20"W x 20"D	20"W x 20"D	24"W x 24"D	24"W x 24"D	32"W x 28"D
Synergy [®] Seat-to-Floor Range	N/A	N/A	N/A	N/A	N/A	N/A	17.25-19.25"	15.75-17.75"	15.875-17.875"	15.75-17.75"	17.25-19.75"	17.25-19.25"
Power Elevating Seat	Standard	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
TRU-Balance [®]	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Specialty Controls	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Yes
Standard Electronics	40A, PG VR2	50A, PG, VSI	40A, PG GC3	40A, PG GC3	40A, PG GC3	40A, PG GC3	40A, PG GC3	40A, Dynamic LiNX	50A, Dynamic LiNX	50A, Dynamic LiNX	50A, Dynamic LiNX	90A, PG VR2
Battery Size (2 required)	12 volt, U-1 (std.), 40 Ah (optional)	(1) 25.2V 18Ah lithium ion, (1) 25.2V 10.4 Ah lithium ion travel battery	18 Ah, 12 volt, deep-cycle	EVO 613 Li: (1) 25.6V, 32.4 Ah lithium iron phosphate EVO 613: (2) 12 volt, U-1	18 Ah, 12 volt, deep-cycle	12 volt, U-1	12 volt, U-1	12 volt, NF-22	12 volt, NF-22	12 volt, NF-22	12 volt, NF-22	12 volt, Group 24
Standard Battery Charger	5A, off-board	2-amp, off-board	2A, off-board	3.5A, off-board	2A, off-board	3.5A, off-board	3.5A, off-board	5A, off-board	5A, off-board	5A, off-board	5A, off-board	8A, off-board
Per-Charge Range ^{3,6}	Up to 15 miles at 300 lbs. Up to 16.6 miles at 220 lbs.	Up to 5 miles (220 lbs.)(10.4 Ah) Up to 8.6 miles (220 lbs.) (18 Ah) Up to 4.6 miles (250 lbs. (10.4 Ah) Up to 7.9 miles (250 lbs.) (18 Ah)	Up to 8.7 miles (300 lbs.) Up to 13.2 miles (200 lbs.)	EVO 613 Li: Up to 21 miles at 200 lbs. Up to 17.6 miles at 300 lbs. EVO 613: Up to 17.1 miles at 200 lbs. Up to 14 miles at 300 lbs.	Up to 8.6 miles	Up to 15 miles	Up to 19.4 miles	Up to 18 miles (300 lbs.) Up to 21 miles (200 lbs.)	Up to 24.8 miles (300 lbs.) Up to 29.5 miles (200 lbs.)	Up to 14.4 miles	Up to 14 miles	Up to 16.5 miles
Battery Weight ⁸	24.5 lbs. (U-1), 32.5 lbs. each (40Ah)	7.6 lbs. (18 Ah), 5.2 lbs (10.4 Ah travel battery)	14 lbs. each	EVO 613 Li: 18.5 lbs. EVO 613: 23.5 lbs. each (2)	14 lbs. each	25 lbs. each	25.2 lbs. each	37 lbs. each	37 lbs. each	37 lbs. each	38 lbs. each	52 lbs. each
Weight of Heaviest Piece ⁵	202 lbs. (with seat) ⁹	59.8 lbs. (unit doesn't disassemble) ¹⁰	36 lbs.	94 lbs. (base)	36 lbs.	69 lbs.	94 lbs.	99 lbs.	124 lbs.	99 lbs.	122 lbs.	195 lbs.
Standard Seat Weight	41 lbs. sport, high-back	N/A	30 lbs. (18") 32 lbs. (20") compact, foldable	46 lbs. (16") 48 lbs. (18") 50 lbs. (20") memory high-back	18" wide: 29 lbs. ⁴ 20" wide: 32 lbs. ⁴ compact, foldable	50.2 lbs comfort, high-back	50.2 lbs. comfort, high-back	18" wide: 51.8 lbs. 20" wide: 54 lbs. 22" wide: 57.6 lbs. high-back	18" wide: 51.8 lbs. 20" wide: 54 lbs. high-back	18" wide: 51.8 lbs. 20" wide: 54 lbs. high-back	18" wide: 51.8 lbs. 20" wide: 54 lbs. high-back	52 lbs. high-back
Standard Seat Size	16" x 16-18", 18" x 18-20", 20" x 20-22"	17.5" x 16.5"	18" x 17" 20" x 18"	16" x 16-18", 18" x 18-20", 20" x 18-20"	18" x 17", 20" x 18"	16" x 16-18", 18" x 18-20", 20" x 18-20"	16" x 16-18", 18" x 18-20", 20" x 18-20"	18" x 18-20", 20" x 18-20", 22" x 20-22"	18" x 18-20", 20" x 18-20"	18" x 18-20", 20" x 18-20", 22" x 20-22", 24" x 24"	18" x 18-20", 20" x 18-20", 22" x 20-22"	24" x 24"
HCPCS Codes	K0899 POWER MOBILITY DEVICE NOT CODED BY DME PDAC OR DOES NOT MEET CRITERIA	K0899 POWER MOBILITY DEVICE NOT CODED BY DME PDAC OR DOES NOT MEET CRITERIA	K0899 POWER MOBILITY DEVICE NOT CODED BY DME PDAC OR DOES NOT MEET CRITERIA	K0822/K0823 Group 2: Standard	K0821 Group 2: Standard, Portable	K0822/K0823 Group 2: Standard	K0822/K0823 Group 2: Standard	K0822/K0823 Group 2: Standard	K0822/K0823 Group 2: Standard	K0824/K0825 Group 2: Heavy Duty	K0824/K0825 Group 2: Heavy Duty	K0826/K0827 Group 2: Very Heavy Duty K0839 Single Power Very Heavy Duty
Warranty	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month limited on SLA batteries; 3-year limited on lithium batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	Lifetime limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	5-year limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	Lifetime limited on frame; 13-month limited on electronics; 13-month on drive motors; 13-month on batteries	K0826/K0827 Models: Lifetime limited on frame; 13-month limited on electronics; 13-month limited on drive motors; 13-month on batteries K0839 Model: Lifetime limited on frame; 2-year limited on electronics; 18-month limited on drive motors; 13-month on batteries
NOT CODED BY DME PDAC												

1) This product is a FDA Class II Medical Device designed to aid individuals with mobility impairments.
2) Without front riggings.
3) Varies with user weight, terrain, battery type, battery condition and tire pressure.
4) Seat weight includes joystick.
5) Does not include seat or battery weights.
6) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.

7) Maximum weight capacity is reduced to 400 lbs. (181 kg) on 18" deep seat configurations.
8) Battery weight may vary based on manufacturer.
9) Seat weight included (because tools are required to remove seat). Battery weight not included.
10) Seat weight included. Unit does not disassemble.
11) Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of + or - 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

BATTERY HCPCS CODES

U-1 E2365
NF-22 E2361
Group 24 E2363
Lithium E2397
18 AH K0733

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement. The information contained herein is correct at time of publication; we reserve the right to alter specifications without prior notice.