

3M™ DBI-SALA® Standard Safe Bucket

Integrated carabiner and hoisting strap

Instead of rope, which is susceptible to fraying, a heavy-duty hoisting/shoulder strap is built into every Safe Bucket. Each bucket is also equipped with a high-quality and lightweight aluminium twist-lock carabiner load rated for 30 kN (6,700 lbs). There is no need to worry about a knot failing, or a non-locking carabiner which may slip off at a connection point.



Fall Protection for Tools

Puncture resistance

Where you work, durability is non-negotiable. That's why every Safe Bucket features hard composite plating at the bottom to protect it from accidental punctures. A leather sleeve also covers the inserts, protecting them from the elements and harsh work environments.



3M Fall Protection | (00 800 999 55500

	Ø	Closure system	0	Height/diameter	Capacity
1500134	45.4 kg (100 lbs)	Hook and loop	Canvas	38 cm / 31.75 cm (15" / 12.5")	30 L
1500133	45.4 kg (100 lbs)	Drawstring	Canvas	38 cm / 31.75 cm (15" / 12.5")	30 L
1500140	113.4 kg (250 lbs)	Hook and loop	Vinyl	38 cm / 31.75 cm (15" / 12.5")	30 L
1500139	113.4 kg (250 lbs)	Drawstring	Vinyl	38 cm / 31.75 cm (15" / 12.5")	30 L

3M™ DBI-SALA® Hard-Body Safe Bucket Insert



	Description
1500141	Hard-Body Safe Bucket Insert

- Converts a standard soft-body Safe Bucket into a hard-body Safe Bucket.
- Our reusable hard-body Safe Bucket insert keeps your Safe Bucket standing upright, making it easier to stage tools and stay productive.
- Integrated inner pockets allow tools to be holstered and organised quickly.



5 Gallon Safe Bucket



1500135	45.4 kg (100 lbs)

- Used to transport standard 5 gallon buckets.
- 5 gallon plastic buckets clip into the Safe Bucket with a unique hook system.
- When not being used, the Safe Bucket can be flattened for easy storage.
- Unique patent pending locking hook and loop closure system helps ensure that there are no accidental spills during lifting and transportation.

(00 800 999 55500 | www.3M.com/FallProtection