

3M™ DBI-SALA® Mobi-Lok™ Vacuum Anchor provides a tie-off point on virtually any smooth, non-porous surface simply by flipping a switch and waiting for the green light.

Lightweight design (under 10 kg) for easy transport. Fail-safe back-up systems with audio alarms and vacuum level indicator. Rubber seals secure anchor without damaging surface. Weight capacity 136 kg. Can be used with horizontal lifeline systems for added mobility for up to four workers.

Applications



Mobi-Lok Vacuum Anchor
*Primary Unit with
Bottle Attachment



CE EN795 CLASS B

2200126	kg	10.46
---------	----	-------

Mobi-Lok aviation industry self-contained vacuum anchor assembly with bottle attachment and carrying case. It is powered up with a single, on-board 0.8 litre compressed gas bottle (order separately) or a large capacity detached bottle, or shop air. Unit can also power one additional secondary pad.

Mobi-Lok Vacuum Anchor
*Primary Unit without
Bottle Attachment



CE EN795 CLASS B

2200125	kg	8.00
---------	----	------

Mobi-Lok aviation industry self-contained vacuum anchor without bottle attachment for situations where shop air is always available.

Mobi-Lok Vacuum Anchor
*Secondary Unit without
Bottle Attachment



CE EN795 CLASS B

2200127	kg	6.80
---------	----	------

Mobi-Lok aviation industry self-contained vacuum anchor secondary pad for connection to a primary pad.

*All Mobi-Lok anchors come with a case



Mobi-Lok Accessories

	Description	kg
2200085	Compressed Air Bottle	1.46
2200086	Fill Station	0.90
2200087	Scuba Adaptor	1.50
2200130	Secondary Pad Hose Assembly	2.10
2200196	Fill Station Adapter	0.01
2200409	2 Person Lifeline	4.77

Note: These are non-stocked items. Please ask your Customer Services representative for a delivery lead time.

