(€





3M[™] Protecta[®] Viper[™] Vertical Lifeline Rope Grab

- The Viper 2 rope grab is available in 2 variants, AC401 has the addition of a 28 cm extension strap with a self locking carabiner (9509437).
- It's extremely simple opening system means that the Viper 2 can be attached to the rope or removed from it at any location.
- As soon as the connecting carabiner is put back into place the Viper 2 is locked to ensure safe use.

Best Seller AC401			15 kn
	0	Ø	kg
AC400	AJ501	10.5 mm	0.44
AC401	9509437	10.5 mm	0.69

The Viper 2 is supplied with a kernmantle rope and is available with rope options from 5 to 99 m lengths in increments of 5 m.

Viper Vertical Lifeline Rope



	∢···· ≻	kg
AC405	5 m	0.58
AC410	10 m	0.91
AC415	15 m	1.24
AC420	20 m	1.59
AC430	30 m	2.26

Polyamide kernmantle static rope, \emptyset 10.50 mm, with yellow and red wear indicator. Rope end: sewn loop underneath protective sleeve Connector: AJ501, 17 mm opening System breaking strength > 22 kN.

Viper Vertical Lifeline Extension Strap



	∢····≻	₽
AC401/1	200 mm	0.44

Extension strap for Viper Rope Grab with carabiner 17 mm opening and snap hook 18 mm opening.

3M[™] Protecta[®] Viper[™] LT Rope Grab with Carabiner



	kg
AC4000	0.48
The Viper LT Manual Rope Grab is a restraint and fall	

arrest device which can be used in a variety of Vertical and Horizontal applications. With its extremely simple opening system, a user can move effortlessly and safely along a Ø 12.5 mm rope to perform their daily tasks.

Vertical fall arrest 100 kg user. Roof top work restraint use.

Viper LT Rope Grab with Extension



	kg
AC4001	0.56

Vertical fall arrest 100 kg user. Roof top work restraint use. A 175 mm extension strap with self-locking double action snap hook to aid ease of use when rope grab is attached to the harness.

Viper LT Rope Grab with Energy Absorber - Edge Tested





	kg
AC4002	0.48

Vertical fall arrest 140 kg user. Roof top work restraint 100 kg user. Energy absorber for fall arrest applications. Edge Tested Model.

Viper LT Rope

(€

(E



	∢····· ≻	kg
AC4010	10 m	1.00
AC4015	15 m	1.24

Kernmantle rope 12.55 mm dia. 25 kN screw gate carabiner, 17 mm opening.

€ EN353-2