



9601 SEAM COMPOUND

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 04/30/2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : TRUCO 9601 SILICONE SEAM COMPOUND

Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use : Silicone Elastomer

Application Method : See Technical Data Sheet

1.3. Details of the supplier of the safety data sheet

TRUCO Coatings
3033 W. 44th St.
Cleveland, OH 44113

1.4. Emergency telephone numbers

CHEMTREC Emergency number : 800-424-9300

Customer Service TRUCO Coatings : 800-227-4569

SECTION 2: Hazards identification

2.1. Classification of the Substance or mixture

Flam. Liq. 4;H226 : Combustible liquid.

Skin Irrit. 3;H316 : Causes mild skin irritation. (Not adopted by US OSHA)

Eye Irrit. 2;H319 : Causes serious eye irritation.

Skin Sens. 1;H317 : May cause an allergic skin reaction.

Carc. 2;H351 : Suspected of causing cancer.

Repr. 2; H361F : Suspected of damaging fertility.

2.2. Label Elements

Using the Toxicity Data Listed in Section 11 and 12 the product is labeled as follows.



DANGER

H226 : Combustible liquid.

H316 : Causes mild skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H351 : Suspected of causing cancer.

H361f : Suspected of damaging fertility.

9601 SILICONE SEAM COMPOUND

Safety Data Sheet

Revision Date: 04/30/2020 Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

[Prevention]:

- P201** : Obtain special instructions before use.
- P202** : Do not handle until all safety precautions have been read and understood.
- P210** : Keep away from flames / hot surfaces - No smoking.
- P235** : Keep cool.
- P240** : Ground / bond container and receiving equipment.
- P241** : Use explosion-proof electrical / ventilating / light / equipment.
- P242** : Use only non-sparking tools.
- P243** : Take precautionary measures against static discharge
- P261** : Avoid breathing dust / fume / gas / mist / vapors / spray.
- P264** : Wash thoroughly after handling.
- P270** : Do not eat, drink or smoke when using this product.
- P272** : Contaminated work clothing should not be allowed out of the workplace.
- P280** : Wear protective gloves / eye protection / face protection.

[Response]:

- P302+352** : IF ON SKIN: Wash with plenty of soap and water.
- P303+361+353** : IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P305+351+338** : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P308+313** : IF exposed or concerned: Get medical advice / attention.
- P314** : Get Medical advice / attention if you feel unwell.
- P321** : Specific treatment (see information on this label).
- P333+313** : If skin irritation or a rash occurs: Get medical advice / attention.
- P337+313** : If eye irritation persists: Get medical advice / attention.
- P363** : Wash contaminated clothing before reuse.
- P370+378** : In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

- P403+233** : Store in a well-ventilated place. Keep container tightly closed
- P405** : Store locked up.

[Disposal]:

- P501** : Dispose of contents / container in accordance with local / national regulations.

SECTION 3: Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Dimethylsiloxane CAS Number: 0063148-62-9	10 – 25	Aquatic Chronic 2;H411	[1]
Methyltris (methylethylketoximino)silane CAS Number: 0022984-54-9	1.0 – 10	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]

9601 SILICONE SEAM COMPOUND

Safety Data Sheet

Revision Date: 04/30/2020 Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium dioxide CAS Number: 0013463-67-7	1.0 – 10	Not Classified	[1][2]
2-Butanone oxime CAS Number 0000096-29-7	1.0 – 10	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]
Proprietary*	0.10 – 1.0	Skin Irrit. 2;H315 Eye Irrit. 2;H319 Skin Sens. 1;H317 Aquatic Chronic 3;H412	[1]
Cyclotetrasiloxane, octamethyl- CAS Number: 0000556-67-2	0.10 – 1.0	Repr. 2;H361f Aquatic Chronic 4;H413	[1][3]

*In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance. *The full texts of the phrases are shown in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation : Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes : Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin : Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion : If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview : Effects of Overexposure Inhalation: Nasal and respiratory irritation, dizziness, fatigue, unconsciousness, asphyxiation. Ingestion: Can cause gastrointestinal disorders. Skin: Possible irritation, dermatitis, and defatting. Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure. See section 2 for further details.

Eyes : Causes serious eye irritation.

Skin : May cause an allergic skin reaction. Causes mild skin irritation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Water, carbon dioxide, foam or dry powder.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce carbon monoxide, oxides of nitrogen and various hydrocarbon fragments.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

9601 SILICONE SEAM COMPOUND

Safety Data Sheet

Revision Date: 04/30/2020 Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Keep cool.
Ground / bond container and receiving equipment.
Use explosion-proof electrical / ventilating / light / equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

This product is considered combustible and is a fire hazard. It supports combustion and decomposes under fire conditions to give off toxic materials. Do not pour, spill, or store near heat, spark sources, or open flame.

If electrical equipment is involved, the use of foam should be avoided. Use water spray to cool non-involved containers. Wear SCBA with a full-face piece operated in the positive pressure demand mode and full protective clothing (Bunker Gear) when fighting fires.

ERG Guide No. - - - -

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Small spill: Remove with absorbent material. Large spill: Eliminate all ignition sources. Ventilate enclosed areas or wear self-contained breathing apparatus. Recover free liquid in closed containers. Keep out of sewers and water courses. Clean area with absorbent material.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protect from freezing.

See section 2 for further details. – [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that forklift trucks and electrical equipment are protected to the appropriate standard.

Incompatible materials: Avoid strong oxidizing agents, concentrated nitric and sulfuric acids, halogen, and molten sulfur.

Store in a cool, dry place. Keep container tightly closed when not in use.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

9601 SILICONE SEAM COMPOUND

Safety Data Sheet

Revision Date: 04/30/2020 Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control Parameters

Exposure : Use standard protocols for exposure to particulates.

8.2. Exposure controls

Respiratory : If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes : Not normally required.

Skin : Use protective gloves as needed to avoid skin irritation.

Engineering Controls : Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices : Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. – [Prevention]:

SECTION 9: Physical and chemical properties

Appearance : Viscous white or gray Liquid

Odor : Not specified

Odor threshold : Not determined

pH : Not available

Melting point / freezing point : Not determined

Initial boiling point and boiling range : Not determined

Flash Point : 150°F ASTM D93

Evaporation rate (Ether = 1) : Slower than ether

Flammability (solid, gas) : Not applicable

Upper/lower flammability or explosive limits : Lower Explosive Limit: 1.1
Upper Explosive Limit: 5.0

Vapor pressure (Pa) : Not determined

Vapor Density : Not available

Specific Gravity : 1.37 (H₂O = 1)

Solubility in Water : Negligible

Partition coefficient n-octanol/water (Log Know) : Not Measured

Auto-ignition temperature : Not available

Decomposition temperature : Not available

Viscosity (cSt) : Not available

VOC Content : < 100 g/liter

Density : Heavier than air (Air + 1)

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

9601 SILICONE SEAM COMPOUND

Safety Data Sheet

Revision Date: 04/30/2020 Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical Stability

Stable under normal circumstances.

10.3. Possibility of Hazardous Reactions

No data available.

10.4. Conditions to Avoid

Keep away from heat, flam and other potential ignition sources.

10.5. Incompatible Materials

Avoid strong oxidizing agents, concentrated nitric and sulfuric acids, halogen and molten sulfur.

10.6. Hazardous Decomposition Products

High temperatures and fires may produce carbon monoxide, oxides of nitrogen and various hydrocarbon fragments.

SECTION 11: Toxicological information

Acute Toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
2-Butanone oxime – (96-29-7)	930.00, Rat – Category: 4	2,000.00, Rabbit – Category: 4	20.00, Rat – Category: 4	No data available	5,000.00, Rat-Category: 4
Cyclotetrasiloxane, octamethyl- - (556-67-2)	2,000.00, Rat – Category: 4	4,640.00 Rabbit – Category: 5	36.00, Rat – Category: NA	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the products ATE (Acute Toxicity Estimate).

Carcinogen Data

CAS No.	Ingredient	Source	Value
0013463-67-7	Titanium dioxide	IARC	Group 2b: Yes

SECTION 12: Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Dimethylsiloxane - (63148-)	3.16, Ictalurus punctatus	44.50, Daphnia magna	Not Available

9601 SILICONE SEAM COMPOUND

Safety Data Sheet

Revision Date: 04/30/2020 Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

62-9)			
2-Butanone oxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus
Proprietary	597.00, Danio rerio	81.00, Daphnia magna	126.00 (72 hr), Scenedesmus subspicatus
Cyclotetrasiloxane, octamethyl- - (556-67-2)	200.00, Leuciscus idus	25.20, Daphnia magna	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains PBT/vPvB chemicals.

12.6. Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Potentially toxic to aquatic life.

SECTION 13: Disposal considerations

13.1. Waste Treatment Methods

Observe all federal, state and local regulations when disposing of this substance.

SECTION 14: Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: No		
14.6. Special precautions for user	No further information		

SECTION 15: Regulatory Information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

9601 SILICONE SEAM COMPOUND

Safety Data Sheet

Revision Date: 04/30/2020 Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification B3 D2A

US EPA Tier II Hazards **Fire:** Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

Titanium dioxide

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Titanium dioxide

Pennsylvania RTK Substances (>1%):

Titanium dioxide

SECTION 16: Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

This is the latest version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Judgments as to the suitability of information herein for the purchaser's purposes are necessarily the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, TRUCO Coatings, extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the purchaser's intended purpose or for consequences of its use.

End of Document