

GatewayTM

Tel 800 668 9318
Tel 416 298 5700
Fax 416 298 9535
mail@nienkamper.com
www.nienkamper.com



CONFERENCE TABLE AND VOX FORUM[®] INSTALLATION GUIDE

HARDWARE PARTS LIST



ALLAN KEYS

Small 4 mm
For hex socket assembly, to join rails together.
For installing bases to rails.
For installing mounting plate to top.
Large 5 mm
For hex socket assembly, to join rail together.



FLAT HEAD HEX SOCKET ASSEMBLY

4 mm and 5 mm - 2" x 1/4" - 20 and threaded collar.
Joins rails together.



FLAT HEAD HEX SOCKET BOLT

4 mm - 5/8" x 1/4" - 20.
Joins bases to rail.




FLAT HEAD HEX SOCKET BOLT

4 mm - 1" x 1/4" - 20.
Joins mounting plate to top.
Joins bases to top for tables up to 108".



TIGHT JOINT FASTENERS

3 piece assembly plus 1 tightening rod.



WOODEN SPLINE

1/8" x 7/8" x (24" - varies).
Inserts into the edge of multiple segment tops.




MOUNTING PLATE

1/4" x 3" x 4".
Fixes rail to top.




WIRE MANAGEMENT "U" CLIPS

Grey ABS plastic.
Used to secure wires to support rail.



ASSEMBLING SUPPORT RAILS

ATTACHING BASE TO RAILS



1

2



- Large conference tables incorporate support rails in multiple segments.
- Position and assemble connecting joints as shown.
- Matching joints are number coded (circular labels).
- Required hardware: 2" x 1/4" - 20 flat head hex socket assembly.
- Tighten joint, aligning marks as shown.
- Certain table shapes require rails to be assembled at different angles (as marked).

- Place bases on top of rails aligning the holes in the base with factory installed thread locations in the rails.
- Attach and tighten bases to rails.
- Required hardware: 5/8" x 1/4" - 20 flat head hex socket bolt.

ATTACHING BASE DIRECTLY TO TOP

FINISHED BASE ASSEMBLY




3

4




- Top is flipped over and bases are mounted directly to the top into pre-installed threaded inserts.
- Required hardware: 1" x 1/4" - 20 flat head hex socket bolt.
- Flip table over.
- If installing bases in this manner, skip to #8 for Forum installation.

- Flip assembly over to apply top.




JOINING MULTIPLE PIECE TOPS



5

- Position multiple section tops with matching identification numbers onto rails.
- Insert wooden spline into the groove at the seam.
- Insert ball fitting, align with tight joint bolt.
- Start the thread.

6



- Slide tops together, align the top.
- Insert tight joint collar.
- Tighten ball fitting, hand tight.


ATTACHING BASE TO TOP



7

- Insert the mounting plate into the top groove of the rail.
- Slide the plate to align threaded inserts of top with holes in mounting plate.
- Required hardware: 1" x 1/4" - 20 flat head hex bolt.

8



- Unpack the Forum box and retrieve the swivel latches.
- Carefully thread plastic thumbscrews into inserts around the square hole in the top.
- Position Forum in opening and carefully ease up into the square hole.
- Rotate the swivel catches and tighten the thumb screw fasteners.

Note: detailed installation instructions are included with all Vox Forums.


WIRE MANAGEMENT - STRIP



- Begin by mounting adhesive wire management strip behind Forum position, or where required.
- Insert cables in 1 of 3 channels.

WIRE MANAGEMENT - "U" CLIPS

9 10



- Using wire management "U" clips, store and route cables to bases along the rail.


WIRE MANAGEMENT - BASE



- Route cabling through top of transition bracket and down leg.
- Note the bottom of the base also has a through hole.

WIRE MANAGEMENT ACCESSORIES

11 12



- To bring cabling from the under side of the top to the floor, wire management accessories can also be used.
- A variety of models are available.
- Instructions for installing wire management accessories are packaged with each accessory.