

## **FGIS Procedure**

Consumable kit reorder number: 176004113

- Preset the incubator at 30 °C.
- Bring the strip to ambient temperature if necessary.

Do not open the strip pouch until ready to use the strip.

Calibrate the Vertu TOUCH by scanning in the DON-V AQUA Vertu TOUCH barcode \* for the specific commodity and the lot of strips being used. [Barcode remains stored in Vertu TOUCH reader].



Weigh 50 g  $\pm$  0.1 g ground sample into a blender jar. Add 250 mL AQUA solution to the blender jar.



Blend at maximum speed for 1 min. Filter the extract into a clean tube for no more than 5 min.



Add 500 µL of AQUA solution and 100 µL of the filtered extract to a strip test vial, cap, and mix well by vortexing.



Strips must be stored at 2-30 °C (36-86 °F)

Limit of Detection: 0.5 ppm

Range: 0.5-5 ppm (1st strip), 5-30 ppm (2nd strip with second dilution)

\* DON-V **F**: the low range **wheat** method. DON-V G: the high range wheat method. DON-V H: the low range corn method. DON-V I: the high range corn method.

Place DON-V strip cassette into incubator. Cover with lid and incubate for 2 minutes.



Transfer 100 µL diluted extract to the DON-V strip by dropping vertically into the circular opening, close the incubator lid, and develop exactly 5 minutes.



While the strip test develops, enter the sample ID into the Vertu TOUCH reader.

When the 5 minutes has ended, fully insert the DON-V strip into the Vertu TOUCH (the round opening in first) Press [Start Measurement]



on TOUCH screen.

Press [Print] to print the result.

Press [Same Barcode] to run the next test using the same lot of strips. Press [Change Barcode] to change the method or

lot of strips being used.

twice diluted extract.



If display shows >Range, press [Change barcode] to scan or select the High Range barcode DON-V G for wheat or DON-V I for corn for the lot being used. Transfer 100 µL of diluted extract from Step 4 into a new strip test vial. Add 1000 µL of AQUA solution. Mix well by vortexing. Repeat steps 5–8, using this

**Orders:** 

Tel: +1-877.228.4244 +1-417.725.6588

Email: orders@vicam.com

**Technical Support:** Tel: +1.800.338.4381 +1.508.482.4935 Email: techservice@vicam.com

Vaters Vicam