Board-Con Male Connector 180°, 1.27 x 1.27mm, 4 - 100 Position, 2 rows, 2 housings, housing height 1.50mm

PANCON CONNECTORS



TYPE–2





TYPE–1

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE±0.05)





NOTES:
Current Rating: 1,00 Amp
Contact Resistance: 20mΩ max.
Withstand Voltage: 500V AC/DC
Insulation Resistance: 1000MΩ min.
Operation Temperature: -40°C to +105°C

Contact Material: Copper Alloy

OPERATION	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	± 3°
DIM	TOL

B0396-XXXXX

# of Contacts	Type	Plating	Material	Packaging
4 – 100	Type 1 Type 2	Gold Flash 10µ" Gold 15µ" Gold 30µ" Gold Gold Flash/Tin 10µ" Gold/Tin 15µ" Gold/Tin 30µ" Gold/Tin Tin Matte Tin	PA9T	Tray

Dimensions		
	Standard	Customized
A:	1,80mm	
B:	3,00mm	
C:	5,00mm	

REV	DATE	NOTE	NAME
1	09.06.2021	issued	MCS

Pancon GmbH, Siemensstrasse 7, 61267 Neu-Anspach
Tel: +496081-964-0, www.pancon.de