

Catalog # 75

Item number: 10430

**Description:** 

2 Ply 220 3/16in x 1/16in

International Designation:

N/A

Construction:

Compound Top Cover Black SBR
Color Black

Top Cover Thickness (in) (4.83 mm) 3/16 in

Top Cover Description (4.65 min) 3/10 m

Compound Bottom Cover Black SBR

Bottom Cover Thickness (in) (1.59 mm) 1/16 in

Bottom Cover Description Smooth

Number of Plies 2

Overall Gauge (in) (9.14 mm) 23/64 in Unit Weight- lb/PIW 0.1810 lbs/PIW

Carcass Type Poly/Nylon
Compound Black SBR

Temperature Range (°F)- High 225 °F

Temperature Range (°F)- Low -25 °F

**Belt Strength:** 

Tension Rating (PIW) 220 PIW

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% 16.00 in

Tension

Min. Pulley Dia. - Head @ 60 - 79% 14.00 in

Tension

Min. Pulley Dia. - Head @ 59% Tension 10.00 in

or Below

Minimum Pulley Diameter- Tail 10.00 in

Splice Instructions:

Splice Step Size 8.00 in Splice Process Step Hot

Other:

Static Conducting No
Cross Rigid No
High Heat No
Impression Top No

Oil Resistant No
Fire Resistant No

FDA Approved No

Suggested Fasteners:

Flexco Plate/Rivet #140/R5
Flexco Hinged #375 or 550

Alligator Staple 8/A
Clipper Lace 8/A

Alligator Lace N/A

## **Special Characteristics:**

This belt is compounded to provide excellent abrasion resistance and flex life and is the best buy for the majority of conveyor belt applications. Its high-tension synthetic fabrics result in minimum stretch, great fastener holding ability, impact resistance and the highest adhesion between plies and cover.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*

St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



## **GRADE 2**2 PLY 220 PIW 3/16 X 1/16









