

**Catalog #**                      **77d**
**Item number:**                **10500**
**Description:**

3 Ply 330 3/16in x Bare

**International Designation:**

N/A

**Pulley Diameter, Minimum**

Min. Pulley Dia. - Head @ 80 - 100% Tension                      18.00 in

Min. Pulley Dia. - Head @ 60 - 79% Tension                      16.00 in

Min. Pulley Dia. - Head @ 59% Tension or Below                      12.00 in

Minimum Pulley Diameter- Tail                      12.00 in

**Construction:**

Compound Top Cover                      Black SBR

Color                      Black

Top Cover Thickness (in)                      (4.83 mm) 3/16 in

Top Cover Description                      Smooth

Compound Bottom Cover                      Poly/Nylon

Bottom Cover Thickness (in)                      (0.00 mm) 0.00 in

Bottom Cover Description                      Bare

Number of Plies                      3

Overall Gauge (in)                      (9.65 mm) 3/8 in

Unit Weight- lb/PIW                      0.1810 lbs/PIW

Carcass Type                      Poly/Nylon

Compound                      Black SBR

Temperature Range (°F)- High                      225 °F

Temperature Range (°F)- Low                      -25 °F

**Splice Instructions:**

Splice Step Size                      8.00 in

Splice Process                      Step Hot

**Other:**

Static Conducting                      No

Cross Rigid                      No

High Heat                      No

Impression Top                      No

Oil Resistant                      No

Fire Resistant                      No

FDA Approved                      No

**Suggested Fasteners:**

Flexco Plate/Rivet                      #190/R5-1/2

Flexco Hinged                      #550

Alligator Staple                      N/A

Clipper Lace                      N/A

Alligator Lace                      N/A

**Belt Strength:**

Tension Rating (PIW)                      330 PIW

**Special Characteristics:**

Ideal for medium to heavy-duty service in slider bed applications. It was designed for use where no oil or wood terpense are present.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*

<b>St. Louis, MO</b>	<b>Boise, ID</b>	<b>Charlotte, NC</b>	<b>Grand Prairie, TX</b>	<b>Philadelphia, PA</b>	<b>Sacramento, CA</b>	<b>Vancouver, WA</b>	<b>Beltservice Canada</b>	<b>Beltservice de Mexic</b>
800-727-2358	800-423-4469	800-849-2358	800-727-2358	800-777-1314	800-289-2358	800-234-2358	877-210-7423	+52 55 53620434
314-344-8500	208-342-4681	704-949-2100	314-344-8555	215-295-1900	916-419-7191	360-567-4280	905-565-9217	+44 2980 3266

# GRADE 2

3 PLY 330 PIW 3/16 X BARE

**77d**

Catalog Number

**10500**

Part Number



Top Cover View



Bottom Cover View



Ply View



**BELTSERVICE**  
CORPORATION

[beltservice.com](http://beltservice.com)

REV 3/23