

Catalog # 83e
Item number: 50183
Description:
 1 Ply 330 3/16in x 1/16in Straight Warp
International Designation:
 N/A

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% Tension	18.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	16.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	14.00 in
Minimum Pulley Diameter- Tail	14.00 in

Construction:

Compound Top Cover	Black SBR
Color	Black
Top Cover Thickness (in)	(4.76 mm) 3/16 in
Top Cover Description	Smooth
Compound Bottom Cover	Black SBR
Bottom Cover Thickness (in)	(1.59 mm) 1/16 in
Bottom Cover Description	Smooth
Number of Plies	1
Overall Gauge (in)	(9.88 mm) 3/8 in
Unit Weight- lb/PIW	0.2170 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black SBR
Temperature Range (°F)- High	176 °F
Temperature Range (°F)- Low	-13 °F

Splice Instructions:

Splice Step Size	0.00 in
Splice Process	Finger

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Belt Strength:

Tension Rating (PIW)	330 PIW
----------------------	---------

Suggested Fasteners:

Flexco Plate/Rivet	R5
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

N/A

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO 800-727-2358 314-344-8500	Boise, ID 800-423-4469 208-342-4681	Charlotte, NC 800-849-2358 704-949-2100	Grand Prairie, TX 800-727-2358 314-344-8555	Philadelphia, PA 800-777-1314 215-295-1900	Sacramento, CA 800-289-2358 916-419-7191	Vancouver, WA 800-234-2358 360-567-4280	Beltservice Canada 877-210-7423 905-565-9217	Beltservice de Mexic +52 55 53620434 +44 2980 3266
--	--	--	--	---	---	--	---	---

GRADE 2

1 PLY 330 3/16 X 1/16 STRAIGHT WARP

83e

Catalog Number

50183

Part Number



Top Cover View



Bottom Cover View



Ply View



BELTSERVICE
CORPORATION

beltservice.com

REV 3/23