

77f Catalog #

Item number: 10502

Description:

3 Ply 330 3/16in x Bare MOR

International Designation:

N/A

Construction:

Compound Top Cover Black MOR

Color Black

(4.76 mm) 3/16 in Top Cover Thickness (in)

Top Cover Description Smooth

Compound Bottom Cover Poly/Nylon Bottom Cover Thickness (in) (0.00 mm) 0.00 in

Bottom Cover Description Bare

Number of Plies 3

Overall Gauge (in) (9.65 mm) 3/8 in

Unit Weight- lb/PIW 0.1810 lbs/PIW

Carcass Type Poly/Nylon

Black MOR Compound

Temperature Range (°F)- High 225 °F

Temperature Range (°F)- Low -25 °F

Belt Strength:

Tension Rating (PIW) 330 PIW Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% 18.00 in

Tension

Min. Pulley Dia. - Head @ 60 - 79% 16.00 in

Tension

Min. Pulley Dia. - Head @ 59% Tension 12.00 in

or Below

Minimum Pulley Diameter- Tail 12.00 in

Splice Instructions:

Splice Step Size 8.00 in Step Hot

Splice Process

Other:

Static Conducting No Cross Rigid No High Heat No Impression Top No Oil Resistant Yes Fire Resistant No

FDA Approved No

Suggested Fasteners:

Flexco Plate/Rivet #190/R5 Flexco Hinged #550 Alligator Staple N/A N/A Clipper Lace

N/A Alligator Lace

Special Characteristics:

Medium oil resistant belt used to resist light traces of oils and terpenes. Widely used in the lumber and recycling industries. Can be used for some whole grains. Ideal for slider bed applications.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



OIL RESISTANT MOR

3 PLY 330 PIW 3/16 X BARE MOR



10502
Part Number





