



INTERWOVEN PVC SPECIFICATIONS

Catalog # 23a

Item number: 10955

Description:

PVC 120 White Crescent Top x FS FDA

International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

2.00 in

Belt Strength:

Tension Rating (PIW)

120 PIW

Construction:

Compound Top Cover White PVC
Color White

Top Cover Description 1/8" Crescent Shapes

Compound Bottom Cover White PVC

Bottom Cover Description Friction Surface

Number of Plies 1

Overall Gauge (in) (7.14 mm) 9/32 in

Unit Weight- lb/PIW 0.0800 lbs/PIW

Carcass Type Interwoven Polyester

Compound White PVC

Temperature Range (°F)- High 180 °F

Temperature Range (°F)- Low 0 °F

Splice Instructions:

Splice Step No Splice Finger Yes

Other:

Static Conducting No
Cross Rigid No
High Heat No
Impression Top Yes
Oil Resistant Yes
Fire Resistant No
FDA Approved Yes

Suggested Fasteners:

Flexco Plate/Rivet N/A
Flexco Hinged N/A
Alligator Staple #125
Clipper Lace #1
Alligator Lace #7

Special Characteristics:

The crescent shape is ideal for incline conveying, as well as creating a multitude of tiny "buckets" for moving wet materials. The versatile pattern can also be reversed to drain a product while conveying on the incline. Unique pattern is self cleaning, and since the crescents overlap, there is constant contact with return rolls, virtually eliminating bumping and thumping. FDA accepted.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-234-2358 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



WHITE PVC

PVC 120 WHITE CRESCENT TOP X FS FDA



10955

Part Number





