

DRY BULK POWDER CONVEYING SPECIFICATIONS

Catalog # 16g
Item number: 34229

Description:

WearSlide Non-Woven 0.5 CFM Abrasion Resistant

International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

0.00 in

Belt Strength:

Tension Rating (PIW)

60 PIW

Construction:

Compound Top Cover White Nitrile
Color White

Top Cover Thickness (in) (0.00 mm) 0.00 in
Top Cover Description Impregnated

Compound Bottom Cover White Nitrile

Bottom Cover Thickness (in) (0.00 mm) 0.00 in

Bottom Cover Description Impregnated

Number of Plies

Overall Gauge (in) (6.35 mm) 1/4 in

Unit Weight- lb/PIW 0.0600 lbs/PIW

Carcass Type Needled Polyester

Compound White Nitrile

Temperature Range (°F)- High 310 °F

Temperature Range (°F)- Low -60 °F

Splice Instructions:

Splice Step No Splice Finger No

Other:

Static Conducting No
Cross Rigid No
High Heat No
Impression Top No
Oil Resistant No
Fire Resistant No
FDA Approved No

Suggested Fasteners:

Flexco Plate/Rivet N/A
Flexco Hinged N/A
Alligator Staple N/A
Clipper Lace N/A
Alligator Lace N/A

Special Characteristics:

Designed specifically for air gravity conveyors. Used to fluidize dry bulk powders such as: cement, barite, silica, alumina, etc.. Provides several advantages over woven air permeable fabrics because it does not require stretching prior to installation and will not unravel when cut or punched. Abrasion resistant WearSlide combines the best features of non-woven polyester with the durability of rubber.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO Boise, ID 800-727-2358 800-423-4469

208-342-4681

Charlotte, NC 800-849-2358 704-949-2100

, NC Grand Prairie, TX 2358 800-727-2358 100 314-344-8555 Philadelphia, PA 800-777-1314 215-295-1900 **Sacramento, CA** 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280 Beltservice Canada 877-210-7423

905-565-9217



314-344-8500

AIR PERMEABLE FABRIC

WEARSLIDE NON-WOVEN 0.5 CFM ABRASION RESISTANT

16g
Catalog Number

34229

Part Number



Top Cover View Bottom Cover View Ply View

