

**Catalog # 135**
**Item number: 10960**
**Description:**


3 Ply CR135 Black RT AS SFMB

**International Designation:**

E24/3 0/N47 RT Black OSM N AS

**Construction:**

Compound Top Cover	Black Nitrile
Top Cover Thickness (in)	(4.75 mm) 0.1870 in
Top Cover Description	Roughtop
Top Cover Shore	65
Compound Bottom Cover	Polyester
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Bottom Cover Description	Bare
Bottom Cover Shore	N/A
Number of Plies	3
Anti Static	Yes
Overall Gauge (in)	(7.87 mm) 0.3100 in
Unit Weight- lb/PIW	0.1157 lbs/PIW
Material Between Plies	Nitrile
Maximum Width (in)	72 in
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	20 °F

**Pulley Diameter, Minimum**


A) Normal Flex (152.40 mm) 6.0000 in

B) Back Flex (304.80 mm) 12.0000 in

**Belt Strength:**

Pull for 1% Elongation (24 N/mm) 135 lbs/sq in

**Splice Instructions:**

Foil	No
Splice Process	Step Cold
Press Temperature (°F)	300 °F
Press Pressure (psi)	30 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

**Other:**

Cross Rigid	Yes
Impression Top	Yes
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

**Special Characteristics:**

The 135 has a special 3 ply highly cross rigid construction designed for SFMB (Surface Finishing Machine Belt) applications. The belt features a high friction, non-marking, oil resistant cover and a low friction bottom fabric suitable for all sanding systems. Developed for use on machines finishing wood, metal and composites. This belt is designed to lay flat and will not curl on the edges due to the special monofilament carcass. Also a very good belt for materials handling and wood products applications and where a non-marking oil resistant belt is required. Excellent for use in folding rail applications in corrugated box plants.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*

<b>St. Louis, MO</b> 800-727-2358 314-344-8500	<b>Boise, ID</b> 800-423-4469 208-342-4681	<b>Charlotte, NC</b> 800-849-2358 704-949-2100	<b>Grand Prairie, TX</b> 800-727-2358 314-344-8555	<b>Philadelphia, PA</b> 800-777-1314 215-295-1900	<b>Sacramento, CA</b> 800-289-2358 916-419-7191	<b>Vancouver, WA</b> 800-234-2358 360-567-4280	<b>Beltservice Canada</b> 877-210-7423 905-565-9217	<b>Beltservice de Mexico</b> +52 55 53620434 +44 2980 3266
--	--	--	--	---	---	--	---	--

# LIGHT DUTY SFMB

3 PLY CR135 BLACK RT AS SFMB

**135**

Catalog Number

**10960**


Part Number



Top Cover View



Bottom Cover View



Ply View



**BELTSERVICE**  
CORPORATION

[beltservice.com](http://beltservice.com)

REV 3/23