Catalog # 137

Item number: 10962

Description:

3 Ply CR135 GST AS SFMB


International Designation:

E24/3 0/N31 ST Gray OSM AS

Construction:

Compound Top Cover **Gray Nitrile** Top Cover Thickness (in) (3.18 mm) 0.1250 in Top Cover Description Smooth Top Cover Shore 65 Compound Bottom Cover Polyester Bottom Cover Thickness (in) (0.00 mm) 0.0000 in **Bottom Cover Description** Bare **Bottom Cover Shore** N/A Number of Plies 3 Anti Static No Overall Gauge (in) (6.60 mm) 0.2600 in Unit Weight- lb/PIW 0.1401 lbs/PIW Material Between Plies Nitrile Maximum Width (in) 72 in Temperature Range (°F)- High 180 °F 20 °F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(152.40 mm) 6.0000 in

B) Back Flex

(304.80 mm) 12.0000 in

Belt Strength:

Pull for 1% Elongation

(24 N/mm) 135 lbs/sq in

Splice Instructions:

Foil No Splice Process Step Cold Press Temperature (°F) 300 °F Press Pressure (psi) 30 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid

Yes

Impression Top No Oil Resistant Yes Fire Resistant No FDA Approved No

Special Characteristics:

208-342-4681

The 137 has a special construction designed for SFMB (Surface Finishing Machine Belt) applications. The belt features a high friction, non-marking, oil resistant cover and low friction bottom fabric. Developed for use on machines finishing wood and composites.

*****All Values are nominal and subject to change without notice.****

St. Louis, MO Boise, ID 800-727-2358 800-423-4469

Charlotte, NC 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900

Sacramento, CA 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280

Beltservice Canada 877-210-7423 905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



314-344-8500

LIGHT DUTY SFMB 3 PLY CR135 GST AS SFMB





