

Catalog # **203**
Item number: **29976**
Description:


ZL White Nitrile Smooth Top x Bare FDA

International Designation:

White Nitrile Smooth Top x FS FDA

Construction:

Compound Top Cover	White Nitrile
Top Cover Thickness (in)	(1.20 mm) 0.0472 in
Top Cover Description	Smooth
Top Cover Shore	65
Compound Bottom Cover	Polyester
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Bottom Cover Description	Friction Surface
Bottom Cover Shore	N/A
Number of Plies	1
Anti Static	No
Overall Gauge (in)	(3.20 mm) 0.1260 in
Unit Weight- lb/PIW	0.0683 lbs/PIW
Material Between Plies	Spiral Polyester
Maximum Width (in)	72 in
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum


A) Normal Flex (76.20 mm) 3.0000 in

B) Back Flex (152.40 mm) 6.0000 in

Belt Strength:

Pull for 1% Elongation (26 N/mm) 150 lbs/sq in

Splice Instructions:

Foil	No
Splice Process	n/a
Press Temperature (°F)	0 °F
Press Pressure (psi)	0 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid	Yes
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

Special Characteristics:

ZipLink is a breakthrough in belting design that combines time tested rubber cover materials with a structured spiral mesh that can be easily spliced at any length into a continuous belt without the need for special tools. ZipLink's construction eliminates points of weakness because there is no loss of strength at the splice area. The recommended working tension of all ZipLink belts is 150lbs/in with very little stretch to the polyester mesh. This belt is stocked at 72" wide and can easily ship within 3 working days.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO	Boise, ID	Charlotte, NC	Grand Prairie, TX	Philadelphia, PA	Sacramento, CA	Vancouver, WA	Beltservice Canada	Beltservice de Mexico
800-727-2358	800-423-4469	800-849-2358	800-727-2358	800-777-1314	800-289-2358	800-234-2358	877-210-7423	+52 55 53620434
314-344-8500	208-342-4681	704-949-2100	314-344-8555	215-295-1900	916-419-7191	360-567-4280	905-565-9217	+44 2980 3266

INDUSTRIAL & FOOD GRADE BELTING


ZL WHITE NITRILE SMOOTH TOP X FS FDA

203

Catalog Number

29976

Part Number



Top Cover View



Bottom Cover View



Ply View



BELTSERVICE
CORPORATION

beltservice.com

REV 3/23