Catalog # 204W

Item number: 33293

Description:

ZL Tan NR Diamond Impression x FS


International Designation:

Tan NR Diamond Impression x FS

Construction:

Compound Top Cover Tan NR Top Cover Thickness (in) (5.60 mm) 0.2205 in Top Cover Description Wedgegrip Top Cover Shore 40 Tan NR Compound Bottom Cover (0.00 mm) 0.0000 in Bottom Cover Thickness (in) **Bottom Cover Description** Friction Surface **Bottom Cover Shore** N/A Number of Plies Anti Static No Overall Gauge (in) (7.20 mm) 0.2834 in Unit Weight- lb/PIW 0.1250 lbs/PIW Spiral Polyester Material Between Plies Maximum Width (in) 72 in Temperature Range (°F)- High 250 °F 0°F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(101.60 mm) 4.0000 in

B) Back Flex

(203.20 mm) 8.0000 in

Belt Strength:

Pull for 1% Elongation

(26 N/mm) 150 lbs/sq in

Splice Instructions:

Foil No Splice Process n/a Press Temperature (°F) 0°F Press Pressure (psi) 0 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid

Yes

Impression Top Yes Oil Resistant No Fire Resistant No FDA Approved No

Special Characteristics:

N/A

*****All Values are nominal and subject to change without notice.****

St. Louis, MO Boise, ID 800-727-2358 800-423-4469

208-342-4681

Charlotte, NC 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900

Sacramento, CA 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280

Beltservice Canada 877-210-7423 905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



314-344-8500

INDUSTRIAL & FOOD GRADE BELTING

ZL TAN NATURAL RUBBER WEDGEGRIP X FS



33293

Part Number









Top Cover View Bottom Cover View Ply View

