

Catalog # 2

10374 Item number:

Description:

3 Ply 15oz White Nitrile COS **International Designation:**

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

2.50 in

Belt Strength:

Tension Rating (PIW)

52 PIW

Construction:

Compound Top Cover White Nitrile Color White Top Cover Thickness (in) (1.19 mm) 3/64 in Top Cover Description Smooth Compound Bottom Cover White Nitrile

Bottom Cover Thickness (in)

Friction Surface **Bottom Cover Description**

Number of Plies

Overall Gauge (in) (3.18 mm) 1/8 in

Unit Weight- lb/PIW 0.0750 lbs/PIW

Carcass Type Cotton-Polyester

White Nitrile Compound

Temperature Range (°F)- High 250 °F

0°F Temperature Range (°F)- Low

Splice Instructions:

Splice Step Splice Finger Yes No

Other:

(0.00 mm) 0.00 in

3

Static Conducting No Cross Rigid No High Heat No Impression Top No Oil Resistant Yes Fire Resistant No Yes FDA Approved

Suggested Fasteners:

Flexco Plate/Rivet N/A Flexco Hinged N/A #62 Alligator Staple Clipper Lace #1 #7 **Alligator Lace**

Special Characteristics:

General purpose food handling; assembly line and packaging belts; resistant to food acids, fats and alkalies. Nitrile compound is also known as a Buna-N and Hycar. Easy-to-clean, smooth 3/64" cover. FDA approved. Construction features tightly woven blend of cotton and polyester plies impregnated and covered with nitrile.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO 800-727-2358 314-344-8500 Boise, ID 800-423-4469 208-342-4681

Charlotte, NC 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900

Sacramento, CA 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280

Beltservice Canada 877-210-7423

905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



National Industrial Belting Association

©Beltservice Corp.

FOOD BELTS3 PLY 15 OZ. WHITE NITRILE COS

2 Catalog Number 10374
Part Number





