

BELTSERVICE LIGHT DUTY SPECIFICATIONS

Catalog # 6

Item number: 10398

Description:

3 Ply Poly 90 White Nitrile COS

International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

2.00 in

Belt Strength:

Tension Rating (PIW)

90 PIW

Construction:

Compound Top Cover White Nitrile
Color White
Top Cover Thickness (in) (0.79 mm) 1/32 in
Top Cover Description Smooth

Compound Bottom Cover

Bottom Cover Thickness (in) (0.00 mm) 0.00 in

Bottom Cover Description Friction Surface

Number of Plies

Overall Gauge (in) (2.38 mm) 3/32 in

Unit Weight- lb/PIW 0.0620 lbs/PIW

Carcass Type

Compound White Nitrile

Temperature Range (°F)- High 250 °F

Temperature Range (°F)- Low 0 °F

Splice	Instru	ctions
--------	--------	--------

Splice Step Yes
Splice Finger No

Other:

White Nitrile

3

N/A

Static Conducting No
Cross Rigid No
High Heat No
Impression Top No
Oil Resistant Yes
Fire Resistant No
FDA Approved Yes

Suggested Fasteners:

Flexco Plate/Rivet N/A
Flexco Hinged N/A
Alligator Staple N/A
Clipper Lace #1A
Alligator Lace #7

Special Characteristics:

High-strength polyester carcass has great dimensional stability for less stretch and better tracking. Thin and flexible for small pulleys. Can be hot water and steam cleaned. FDA accepted.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO 800-727-2358 314-344-8500

Boise, ID 800-423-4469 208-342-4681

Charlotte, NC 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900 **Sacramento, CA** 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280 Beltservice Canada 877-210-7423

905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



FOOD BELTS 3 PLY POLY 90 WHITE NITRILE COS









