

Catalog # 8

10390 Item number:

**Description:** 

3 Ply Poly 150 White Nitrile FDA COS

**International Designation:** 

N/A

**Pulley Diameter, Minimum** 

Minimum Pulley Diameter

2.50 in

**Belt Strength:** 

Tension Rating (PIW)

150 PIW

Construction:

Compound Top Cover White Nitrile Color White Top Cover Thickness (in) (1.19 mm) 3/64 in Top Cover Description Smooth Compound Bottom Cover White Nitrile

Bottom Cover Thickness (in)

(0.00 mm) 0.00 in Friction Surface **Bottom Cover Description** 

Number of Plies

Overall Gauge (in) (3.97 mm) 5/32 in

Unit Weight- lb/PIW 0.0750 lbs/PIW

Carcass Type **RFL** Polyester

White Nitrile Compound

Temperature Range (°F)- High 250 °F

0°F Temperature Range (°F)- Low

**Splice Instructions:** 

Splice Step Yes Splice Finger No

Other:

Static Conducting No Cross Rigid No High Heat No Impression Top No Oil Resistant Yes Fire Resistant No Yes FDA Approved

**Suggested Fasteners:** 

Flexco Plate/Rivet N/A Flexco Hinged N/A #125 Alligator Staple Clipper Lace #2 #15 **Alligator Lace** 

## **Special Characteristics:**

Thicker, stronger version of the Poly White Nitrile Series; features heavier, stronger polyester fabric RFL treated for greater adhesion under rugged conditions; also heavier skim coats between plies and a superior wear-resistant nitrile cover; usual advantages of 100% polyester carcass. Can be hot water and steam cleaned. FDA approved.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*

St. Louis, MO 800-727-2358 314-344-8500 Boise, ID 800-423-4469 208-342-4681

Charlotte, NC 800-849-2358 704-949-2100

**Grand Prairie, TX** 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900

3

Sacramento, CA 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280

**Beltservice Canada** 877-210-7423

905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



## **FOOD BELTS**3 PLY POLY 150 WHITE NITRILE COS

Catalog Number

10390
Part Number





