

Catalog # 10

Item number: 10402

Description:

3 Ply Poly 105 White Teflon FDA COS

International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

2.50 in

Belt Strength:

Tension Rating (PIW)

105 PIW

Yes

No

Construction:

Compound Top Cover White Teflon Color White Top Cover Thickness (in) (0.05 mm) 0.00 in Top Cover Description Teflon Compound Bottom Cover White Nitrile

Bottom Cover Thickness (in)

(0.00 mm) 0.00 in Friction Surface **Bottom Cover Description**

Number of Plies

Overall Gauge (in) (1.59 mm) 1/16 in

Unit Weight- lb/PIW 0.0500 lbs/PIW

Carcass Type Polyester

White Nitrile Compound

Temperature Range (°F)- High 250 °F

0°F Temperature Range (°F)- Low

Splice Instructions:

Splice Step Splice Finger

Other:

Static Conducting No Cross Rigid No High Heat No Impression Top No Oil Resistant Yes Fire Resistant No Yes FDA Approved

Suggested Fasteners:

Flexco Plate/Rivet N/A Flexco Hinged N/A #62 Alligator Staple Clipper Lace #1XSP #1 **Alligator Lace**

Special Characteristics:

Excellent for wet, sticky materials and operations involving gluing, coating, spreading; best release characteristics. The slippery top surface is created by the thin teflon film. Carcass is strong and flexible. FDA accepted.

3

*****All Values are nominal and subject to change without notice.****

St. Louis, MO 800-727-2358 314-344-8500

Boise, ID 800-423-4469 208-342-4681

Charlotte, NC 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900

Sacramento, CA 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280

Beltservice Canada 877-210-7423 905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



National Industrial Belting Association

©Beltservice Corp.

FOOD BELTS3 PLY POLY 105 WHITE TEFLON COS









