

BELTSERVICE LIGHT DUTY SPECIFICATIONS

Catalog # 15a

Item number: Description:

3 Ply 150 Tan Nitrile COS International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

3.00 in

Belt Strength:

Tension Rating (PIW)

150 PIW

Yes

No

Construction:

Compound Top Cover Tan Nitrile
Color Tan
Top Cover Thickness (in) (0.79 mm) 1/32 in
Top Cover Description Smooth
Compound Bottom Cover Tan Nitrile
Bottom Cover Thickness (in) (0.00 mm) 0.00 in

10692

Bottom Cover Description Friction Surface

Number of Plies

Overall Gauge (in) (3.57 mm) 9/64 in

Unit Weight- lb/PIW 0.0700 lbs/PIW

Carcass Type Polyester

Compound Tan Nitrile

Temperature Range (°F)- High 250 °F

Temperature Range (°F)- Low 0 °F

Splice Instructions:

Splice Step
Splice Finger

Other:

Static Conducting No
Cross Rigid No
High Heat No
Impression Top No
Oil Resistant Yes
Fire Resistant No
FDA Approved Yes

Suggested Fasteners:

Flexco Plate/Rivet N/A
Flexco Hinged N/A
Alligator Staple #125
Clipper Lace #2
Alligator Lace #15

Special Characteristics:

Tan belts are popular on inspection lines because they are less tiresome on the inspectors' eyes. Also, tan is commonly used in fruit and vegetable processing because of its greater resistance to staining. This belt features a strong, all polyester carcass and is FDA accepted.

3

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO 800-727-2358 314-344-8500

Boise, ID 800-423-4469 208-342-4681 Charlotte, NC 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900 Sacramento, CA 800-289-2358 916-419-7191 Vancouver, WA 800-234-2358 360-567-4280 **Beltservice Canada** 877-210-7423

905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



FOOD BELTS 3 PLY 150 TAN NITRILE COS



10692 **Part Number**





