



Catalog # 26a
Item number: 10716

Item number: Description:

9 Ply Brown Nitrile FBS

International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

4.00 in

Belt Strength:

Tension Rating (PIW)

108 PIW

Construction:

Compound Top Cover

Color

Brown

Top Cover Thickness (in)

Top Cover Description

Compound Bottom Cover

Bottom Cover Thickness (in)

Cotton-Polyester

Cotton-Polyester

Cotton-Polyester

Cotton-Polyester

Bottom Cover Description Friction Surface

Number of Plies 9

Overall Gauge (in) (5.16 mm) 13/64 in

Unit Weight- lb/PIW 0.1000 lbs/PIW

Carcass Type Cotton-Polyester

Compound Brown Nitrile

Temperature Range (°F)- High 250 °F

Temperature Range (°F)- Low 0 °F

Splice Instructions:

Splice Step Yes
Splice Finger No

Other:

Static Conducting No
Cross Rigid No
High Heat No
Impression Top No
Oil Resistant Yes
Fire Resistant No
FDA Approved No

Suggested Fasteners:

Flexco Plate/Rivet N/A
Flexco Hinged N/A
Alligator Staple #187
Clipper Lace #3
Alligator Lace #27

Special Characteristics:

Features a tighly woven blend of cotton and polyester plies impregnated with nitrile, producing a belt suitable for light and medium-weight conveying for a multitude of applications. Particularly popular for oily conditions, especially the conveying of metal parts, also as carrying tapes for folding machines. Economical. Very flexible.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO 800-727-2358 314-344-8500

Boise, ID 800-423-4469 208-342-4681 **Charlotte, NC** 800-849-2358 704-949-2100

Grand Prairie, TX 800-727-2358 314-344-8555

Philadelphia, PA 800-777-1314 215-295-1900 **Sacramento, CA** 800-289-2358 916-419-7191

Vancouver, WA 800-234-2358 360-567-4280

Beltservice Canada 877-210-7423

905-565-9217

Beltservice de Mexico +52 55 53620434

+44 2980 3266



LIGHT DUTY9 PLY BROWN NITRILE FBS









