

BELTSERVICE LIGHT DUTY SPECIFICATIONS

Catalog # 28

Item number: 10708

Description:

5 Ply Poly 225 Blk Heavy Duty Nitrile FBS

International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter

3.00 in

Belt Strength:

Tension Rating (PIW)

225 PIW

Construction:

Unit Weight- lb/PIW

Compound Top Cover Polyester
Color Black
Top Cover Thickness (in) (0.00 mm) 0.00 in
Top Cover Description Friction Surface
Compound Bottom Cover Polyester

Bottom Cover Thickness (in) (0.00 mm) 0.00 in

Bottom Cover Description Friction Surface

Number of Plies 5

Overall Gauge (in) (4.37 mm) 11/64 in

Carcass Type Polyester

Compound Black Nitrile

Temperature Range (°F)- High 250 °F

Temperature Range (°F)- Low 0 °F

Splice Instructions:

Splice Step Yes
Splice Finger No

Other:

Static Conducting

Cross Rigid

No

High Heat

No

Impression Top

Oil Resistant

Fire Resistant

No

FDA Approved

No

Suggested Fasteners:

Flexco Plate/Rivet N/A
Flexco Hinged N/A
Alligator Staple N/A
Clipper Lace #3
Alligator Lace #20

Special Characteristics:

These belts are recommended for handling metal stampings, automotive parts, sheet steel and any application requiring very high oil resistance. Features rugged, high-strength polyester carcass; suitable for medium-capacity transmission belt where oil, grease or chemicals are present. Flexible, yet will withstand cutting, gouging and abrasion.

0.0940 lbs/PIW

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexico 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



LIGHT DUTY5 PLY POLY 225 PIW BLACK HEAVY DUTY NITRILE FBS

28
Catalog Number

10708

Part Number





