

Catalog # **51**
Item number: **10462**
Description:
 2 Ply 220 Tan Bare x Bare
International Designation:
 N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter 8.00 in

Belt Strength:

Tension Rating (PIW) 220 PIW

Construction:

Compound Top Cover	Poly/Nylon
Color	Tan
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	Bare
Compound Bottom Cover	Poly/Nylon
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	2
Overall Gauge (in)	(3.97 mm) 5/32 in
Unit Weight- lb/PIW	0.0690 lbs/PIW
Carcass Type	Polyester
Compound	Black SBR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	R2
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	N/A
Alligator Lace	#15

Special Characteristics:

This belt features a high-strength 2 ply polyester-nylon carcass. It is ideal for applications requiring a low coefficient of friction on both the top and bottom.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO	Boise, ID	Charlotte, NC	Grand Prairie, TX	Philadelphia, PA	Sacramento, CA	Vancouver, WA	Beltservice Canada	Beltservice de Mexico
800-727-2358	800-423-4469	800-849-2358	800-727-2358	800-777-1314	800-289-2358	800-234-2358	877-210-7423	+52 55 53620434
314-344-8500	208-342-4681	704-949-2100	314-344-8555	215-295-1900	916-419-7191	360-567-4280	905-565-9217	+44 2980 3266

PACKAGE HANDLING

2 PLY 220 PIW TAN BARE X BARE

51

Catalog Number

10462

Part Number



Top Cover View



Bottom Cover View



Ply View



BELTSERVICE
CORPORATION

beltservice.com

REV 3/23