

Catalog # 55a

Item number: **Description:** 

2 Ply 210 Gray Roughtop x Bare

**International Designation:** 

N/A

**Pulley Diameter, Minimum** 

Minimum Pulley Diameter

6.00 in

**Belt Strength:** 

Tension Rating (PIW)

210 PIW

Construction:

Gray SBR Compound Top Cover

10620

Color Gray

Top Cover Thickness (in) (0.00 mm) 0.00 in Top Cover Description Roughtop

Bare RFL Compound Bottom Cover

Bottom Cover Thickness (in) (0.00 mm) 0.00 in

**Bottom Cover Description** Bare

Number of Plies 2

Overall Gauge (in) (7.94 mm) 5/16 in

0.1060 lbs/PIW Unit Weight- lb/PIW

Carcass Type Polyester

Compound Gray SBR

250 °F Temperature Range (°F)- High

Temperature Range (°F)- Low -40 °F **Splice Instructions:** 

Splice Step Yes Splice Finger No

Other:

Static Conducting No Cross Rigid No High Heat No Impression Top Yes Oil Resistant No Fire Resistant No FDA Approved No

**Suggested Fasteners:** 

Flexco Plate/Rivet N/A Flexco Hinged N/A Alligator Staple #125 Clipper Lace #2 #15 Alligator Lace

## **Special Characteristics:**

The Gray roughtop is non-markings and is constructed of two plies of high-strength, all-synthetic polyester fabrics. Very flexible, low stretch and moisture resistant incline/decline belt.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*

St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



## **INCLINE ROUGHTOP**

2 PLY 210 PIW GRAY ROUGHTOP X BARE



10620

**Part Number** 





