

Catalog # 57

Item number: 10680

Description:

4 Ply CP30 Black Roughtop x FS

International Designation:

N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter 4.00 in

Belt Strength:

Tension Rating (PIW)

112 PIW

Construction:

Black SBR Compound Top Cover

Black Color

Top Cover Thickness (in) (0.00 mm) 0.00 in

Top Cover Description Roughtop

Compound Bottom Cover Black SBR

Bottom Cover Thickness (in) (0.00 mm) 0.00 in

Bottom Cover Description Friction Surface

Number of Plies

Overall Gauge (in) (10.32 mm) 13/32 in

Unit Weight- lb/PIW 0.1100 lbs/PIW

Carcass Type Cotton-Polyester

Compound Black SBR

250 °F Temperature Range (°F)- High

Temperature Range (°F)- Low -40 °F **Splice Instructions:**

Splice Step Yes Splice Finger No

Other:

Static Conducting No Cross Rigid No High Heat No Impression Top Yes Oil Resistant No Fire Resistant No FDA Approved No

Suggested Fasteners:

Flexco Plate/Rivet N/A Flexco Hinged N/A Alligator Staple #125 Clipper Lace #1 #15 Alligator Lace

Special Characteristics:

Long a popular standard in the industry. The cotton/polyester blend carcass gives a hefty appearance and cushioning effect.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



National Industrial Belting Association

©Beltservice Corp.

INCLINE ROUGHTOP

4 PLY CP30 BLACK ROUGHTOP X FS

57
Catalog Number

10680

Part Number

Top Cover View **Bottom Cover View** Ply View

