

Catalog # **63**
Item number: **10654**
Description:
 3 Ply CP30 Black Duralift x FS
International Designation:
 N/A

Pulley Diameter, Minimum

Minimum Pulley Diameter 3.00 in

Belt Strength:

Tension Rating (PIW) 90 PIW

Construction:

Compound Top Cover	Black SBR
Color	Black
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	1/4" Inverted V-Ribs
Compound Bottom Cover	Black SBR
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	3
Overall Gauge (in)	(10.32 mm) 13/32 in
Unit Weight- lb/PIW	0.1250 lbs/PIW
Carcass Type	Cotton-Polyester
Compound	Black SBR
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	-40 °F

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#7

Special Characteristics:

Long wearing, solid inverted V-shaped ridges prevent back sliding on high inclines. Self-cleaning belt is popular as case conveyor in bottling industry.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO	Boise, ID	Charlotte, NC	Grand Prairie, TX	Philadelphia, PA	Sacramento, CA	Vancouver, WA	Beltservice Canada	Beltservice de Mexic
800-727-2358	800-423-4469	800-849-2358	800-727-2358	800-777-1314	800-289-2358	800-234-2358	877-210-7423	+52 55 53620434
314-344-8500	208-342-4681	704-949-2100	314-344-8555	215-295-1900	916-419-7191	360-567-4280	905-565-9217	+44 2980 3266

INCLINE SPECIALTY



3 PLY CP30 BLACK DURALIFT X FS

63

Catalog Number

10654


Part Number



Top Cover View



Bottom Cover View



Ply View



BELTSERVICE
CORPORATION

beltservice.com

REV 3/23