Catalog # **103RCAS**

Item number: 10750


Description:

1 PUR B 35 MAT / ALCW **International Designation:** E5/1 U0/U2 White Matte AS

Construction:

Compound Top Cover White PU Top Cover Thickness (in) (0.20 mm) 0.0080 in **Top Cover Description** Matte Top Cover Shore 86 Polyester Compound Bottom Cover (0.00 mm) 0.0000 in Bottom Cover Thickness (in) **Bottom Cover Description** PU Impregnated **Bottom Cover Shore** N/A Number of Plies 1 Anti Static Yes Overall Gauge (in) (0.71 mm) 0.0280 in 0.0117 lbs/PIW Unit Weight- lb/PIW Material Between Plies N/A Maximum Width (in) 79 in 176 °F Temperature Range (°F)- High 8°F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(4.06 mm) 0.1600 in

B) Back Flex

(7.87 mm) 0.3100 in

Belt Strength:

Pull for 1% Elongation

(5 N/mm) 28 lbs/sq in

Splice Instructions:

Foil No Splice Process Finger 315 °F Press Temperature (°F) Press Pressure (psi) 22 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid Yes

Impression Top No Oil Resistant Yes Fire Resistant No FDA Approved Yes

Special Characteristics:

The 103RCAS meets FDA compliance standards. The RC (Release Cover) makes it extremely good in applications where material release is important. The 103RCAS has a PU top cover giving it high abrasion resistance in addition to the high release properties. This belt is resistant to mineral and vegetable oils, fats, detergents. The 103RCAS is highly thermal conductive making it excellent for cooling tunnels and is also anti static

*****All Values are nominal and subject to change without notice.*****

Boise, ID Sacramento, CA St. Louis, MO Charlotte, NC Grand Prairie, TX Philadelphia, PA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 800-727-2358 208-342-4681 215-295-1900 +44 2980 3266 314-344-8500 704-949-2100 314-344-8555 916-419-7191 360-567-4280 905-565-9217



URETHANE COVERS FDA

1 PUR B 35 MAT/ALCW

INTERNATIONAL DESIGNATION: E5/1 U0/U2 WHITE MATTE AS





