Catalog # 103F ltem number: 42448

Description:

1 Ply Poly 23 Light Green FS X FS FDA


International Designation:

E4/1 U0/U0 Light Green FDA

Construction:

Compound Top Cover PU Impregnated Top Cover Thickness (in) (0.00 mm) 0.0000 in Top Cover Description PU Impregnated Top Cover Shore N/A PU Impregnated Compound Bottom Cover Bottom Cover Thickness (in) (0.00 mm) 0.0000 in **Bottom Cover Description** PU Impregnated **Bottom Cover Shore** N/A Number of Plies 1 Anti Static No Overall Gauge (in) (0.60 mm) 0.0236 in 0.0075 lbs/PIW Unit Weight- lb/PIW Material Between Plies N/A Maximum Width (in) 72 in Temperature Range (°F)- High 176 °F -4 °F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(6.30 mm) 0.2480 in

B) Back Flex

(6.30 mm) 0.2480 in

Belt Strength:

Pull for 1% Elongation

(4 N/mm) 22 lbs/sq in

Splice Instructions:

Foil Yes
Splice Process Finger
Press Temperature (°F) 320 °F
Press Pressure (psi) 29 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid No

Impression Top No
Oil Resistant No
Fire Resistant No
FDA Approved Yes

Special Characteristics:

#103F is used primarily in chocolate enrobing and weigh scale operations. It can be used with very tight transfers with its minimum pulley diameter rating of 6.3mm.

*****All Values are nominal and subject to change without notice.*****

Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Vancouver, WA **Beltservice Canada** Beltservice de Mexico St. Louis, MO Boise, ID Sacramento, CA 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 905-565-9217 314-344-8500 704-949-2100 215-295-1900 360-567-4280 208-342-4681 314-344-8555 916-419-7191 +44 2980 3266



BARE/FABRIC COVERED FDA

1 PLY POLY 23 LIGHT GREEN FS X FS FDA INTERNATIONAL DESIGNATION: E4/1 U0/U0 LIGHT GREEN FDA



42448 **Part Number**

