

LIGHTWEIGHT THERMOPLASTIC SPECIFICATIONS

Catalog # 2B20 Item number: 41997

Description:

2 Ply Poly 69 Clear PO x FS AS FDA


International Designation:

ES 12/2 PO0/PO6 Clear AS FDA

Construction:

Compound Top Cover Thermoplastic Polyolefine Top Cover Thickness (in) (0.60 mm) 0.0236 in **Top Cover Description** Matte Top Cover Shore 90 PO Impregnated Compound Bottom Cover Bottom Cover Thickness (in) (0.00 mm) 0.0000 in **Bottom Cover Description Impregnated Bottom Cover Shore** N/A Number of Plies 2 Anti Static Yes Overall Gauge (in) (2.60 mm) 0.1024 in Unit Weight- lb/PIW 0.0410 lbs/PIW Material Between Plies Thermoplastic Polyolefine Maximum Width (in) 118 in Temperature Range (°F)- High 140 °F -4 °F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(80.00 mm) 3.1496 in

B) Back Flex

(120.00 mm) 4.7244 in

Belt Strength:

Pull for 1% Elongation

(12 N/mm) 68 lbs/sq in

Splice Instructions:

Foil No
Splice Process Finger
Press Temperature (°F) 260 °F
Press Pressure (psi) 22 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid Yes

Impression TopNoOil ResistantYesFire ResistantNoFDA ApprovedYes

Special Characteristics:

#2B20 has a high release thermoplastic Polyolefin cover that is suitable for conveying tobacco and any sticky food product. It is also perfect for use in wood finishing plants on spray booth conveyors where stain and lacquer overspray needs to be wiped from the belt surface.

*****All Values are nominal and subject to change without notice.*****

Grand Prairie, TX Sacramento, CA St. Louis, MO Boise, ID Charlotte, NC Philadelphia, PA **Beltservice Canada** Beltservice de Mexic Vancouver, WA 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



POLYOLEFIN FDA

2 PLY POLY 69 CLEAR PO X FS AS FDA

INTERNATIONAL DESIGNATION: ES 12/2 P00/P06 CLEAR AS FDA



41997
Part Number





