Catalog # **304QFR**

Item number: 49025

Description:

3 Ply 200 MONO SBR QW x QW FR


International Designation:

PH E30/3 QW/R/QW FR AS

Construction:

Compound Top Cover Bare RFL (0.00 mm) 0.0000 in Top Cover Thickness (in) **Quiet Weave Top Cover Description** Top Cover Shore Bare RFL Compound Bottom Cover (0.00 mm) 0.0000 in Bottom Cover Thickness (in) **Bottom Cover Description Quiet Weave Bottom Cover Shore** N/A Number of Plies 3 Anti Static Yes Overall Gauge (in) (4.01 mm) 0.1580 in 0.0858 lbs/PIW Unit Weight- lb/PIW Material Between Plies SBR Maximum Width (in) 72 in 250 °F Temperature Range (°F)- High -40 °F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(101.60 mm) 4.0000 in

B) Back Flex

(101.60 mm) 4.0000 in

Belt Strength:

Pull for 1% Elongation

(18 N/mm) 100 lbs/sq in

Splice Instructions:

Foil No Splice Process n/a 0°F Press Temperature (°F) Press Pressure (psi) 0 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid Yes

Impression Top No Oil Resistant No Fire Resistant Yes FDA Approved No

Special Characteristics:

#304QFR is a black 3 ply 200 lb. rated rubber monofilament belt with a twill weave low friction surface on both sides. This flame retardant belt is commonly used at package handling facilities and on luggage handling systems at Stocked in 72" width. airports.

*****All Values are nominal and subject to change without notice.*****

Boise, ID St. Louis, MO Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-289-2358 800-234-2358 +52 55 53620434 800-727-2358 800-777-1314 877-210-7423 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



NIBA National Industrial Belting Association

BARE/FABRIC COVERED PVC/RUBBER

3 PLY 200 MONO SBR QW X QW FR INTERNATIONAL DESIGNATION: PH E30/3 QW/R/QW FR AS









