

Catalog # **139a**
Item number: **24230**
Description:


NW 25 Black HC

International Designation:

NW 25 HC SF Black

Construction:

Compound Top Cover	Polyester Fleece
Top Cover Thickness (in)	(0.00 mm) 0.0000 in
Top Cover Description	Smooth
Top Cover Shore	N/A
Compound Bottom Cover	Polyester Fleece
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Bottom Cover Description	Non-Woven
Bottom Cover Shore	N/A
Number of Plies	1
Anti Static	Yes
Overall Gauge (in)	(2.60 mm) 0.1024 in
Unit Weight- lb/PIW	0.0290 lbs/PIW
Material Between Plies	N/A
Maximum Width (in)	79 in
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	14 °F

Pulley Diameter, Minimum


A) Normal Flex (38.10 mm) 1.5000 in

B) Back Flex (38.10 mm) 1.5000 in

Belt Strength:

Pull for 1% Elongation (15 N/mm) 85 lbs/sq in

Splice Instructions:

Foil	No
Splice Process	Skive
Press Temperature (°F)	180 °F
Press Pressure (psi)	18 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Special Characteristics:

This belt is manufactured with a nonwoven construction that is highly conductive, wear and cut resistant, quiet running and offers a soft impact surface. Commonly used in automotive applications, mail and post sorting systems, airport luggage handling and distributions centers. This belt resembles a felt like construction suitable for conveying plastic parts or electronic components.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO 800-727-2358 314-344-8500	Boise, ID 800-423-4469 208-342-4681	Charlotte, NC 800-849-2358 704-949-2100	Grand Prairie, TX 800-727-2358 314-344-8555	Philadelphia, PA 800-777-1314 215-295-1900	Sacramento, CA 800-289-2358 916-419-7191	Vancouver, WA 800-234-2358 360-567-4280	Beltservice Canada 877-210-7423 905-565-9217	Beltservice de Mexic +52 55 53620434 +44 2980 3266
--	--	--	--	---	---	--	---	---

NON WOVEN BELTS

NW 25 BLACK HC



INTERNATIONAL DESIGNATION: NW 25 HC SF BLACK

139A


Catalog Number

24230


Part Number



Top Cover View



Bottom Cover View



Ply View



BELTSERVICE
CORPORATION

beltservice.com

REV 3/23