

LIGHTWEIGHT THERMOPLASTICS SPECIFICATIONS

Catalog # 139C

Item number: 26568

Description: NW 60 Green NA


International Designation:

NW 60 Green NA

Construction:

Compound Top Cover Polyester Fleece Top Cover Thickness (in) (0.00 mm) 0.0000 in **Top Cover Description** Non-Woven Top Cover Shore Polyester Fleece Compound Bottom Cover (0.00 mm) 0.0000 in Bottom Cover Thickness (in) **Bottom Cover Description** Non-Woven **Bottom Cover Shore** N/A Number of Plies 1 Anti Static No Overall Gauge (in) (5.64 mm) 0.2220 in 0.0580 lbs/PIW Unit Weight- lb/PIW Material Between Plies N/A Maximum Width (in) 72 in 250 °F Temperature Range (°F)- High 14 °F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(127.00 mm) 5.0000 in

B) Back Flex

(127.00 mm) 5.0000 in

Belt Strength:

Pull for 1% Elongation

(18 N/mm) 100 lbs/sq in

Splice Instructions:

Foil No
Splice Process Skive
Press Temperature (°F) 180 °F
Press Pressure (psi) 18 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid No

Impression Top No
Oil Resistant Yes
Fire Resistant No
FDA Approved No

Special Characteristics:

This belt is designed for wear and cut resistance, soft impact surface, high temperature resistance up to 250° F, and is quiet running with the felt type construction. Most common industries using this belt are the automotive industry, airports, package handling, packing lines and cutting machines.

*****All Values are nominal and subject to change without notice.*****

Charlotte, NC Boise, ID St. Louis, MO **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 +52 55 53620434 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



NIBA National Industrial Belting Association

©Beltservice Corp.

NON WOVEN BELTS

NW 60 GREEN NA INTERNATIONAL DESIGNATION: NW 60 GREEN NA

139C **Catalog Number**

26568 **Part Number**



