Catalog # 115A

Item number: 10754

Description:

3 Ply Poly 85 Green PVC C x IP

International Designation:

E15/3 V8IP/V7 Green NA

В

Pulley Diameter, Minimum

 $\begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \end{array}$

A) Normal Flex

(99.82 mm) 3.9300 in

B) Back Flex

(139.95 mm) 5.5100 in

Construction:

Compound Top Cover Green PVC Top Cover Thickness (in) (0.70 mm) 0.0275 in **Top Cover Description** Smooth Top Cover Shore 80 Green PVC Compound Bottom Cover Bottom Cover Thickness (in) (0.80 mm) 0.0314 in **Bottom Cover Description** Inverted Pyramid **Bottom Cover Shore** 85 Number of Plies 3 Anti Static No Overall Gauge (in) (4.60 mm) 0.1811 in 0.0833 lbs/PIW Unit Weight- lb/PIW Material Between Plies **PVC** Maximum Width (in) 118 in 180 °F Temperature Range (°F)- High 5°F Temperature Range (°F)- Low

Belt Strength:

Pull for 1% Elongation

(15 N/mm) 86 lbs/sq in

Splice Instructions:

Foil Yes
Splice Process Finger
Press Temperature (°F) 330 °F
Press Pressure (psi) 25 lbs/sq in
Note: Listed above is a quideline only. Every vulcanizer is different and will

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid No

 Impression Top
 No

 Oil Resistant
 No

 Fire Resistant
 No

 FDA Approved
 No

Special Characteristics:

The 115A belt is constructed of a high strength 3 ply monofilament carcass with a smooth 0.07 mm top PVC cover and an 0.08 mm thick inverted pyramid bottom cover. This belt is commonly used for hood wall belts in fiberglass insulation plants. The green PVC covers are ideal for most agricultural applications for transporting food products.

*****All Values are nominal and subject to change without notice.*****

Boise, ID St. Louis, MO Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-423-4469 800-849-2358 +52 55 53620434 800-727-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



NIBA National Industrial Belting Association

PVC/NBR PROFILE/STICKY TOP COVERS

3 PLY POLY 85 GREEN PVC C X IP

INTERNATIONAL DESIGNATION: E15/3 V8IP/V7 GREEN NA









