

Catalog # 139COS
Item number: 50567
Description:


PHSW 125 Black PVC C x B FR

International Designation:

N/A

Construction:

Compound Top Cover	Black PVC
Top Cover Thickness (in)	(0.40 mm) 0.0157 in
Top Cover Description	Gloss
Top Cover Shore	80A
Compound Bottom Cover	Black PVC
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Bottom Cover Description	Brushed
Bottom Cover Shore	N/A
Number of Plies	1
Anti Static	No
Overall Gauge (in)	(4.10 mm) 0.1614 in
Unit Weight- lb/PIW	0.0680 lbs/PIW
Material Between Plies	N/A
Maximum Width (in)	72 in
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	32 °F

Pulley Diameter, Minimum


A) Normal Flex (76.20 mm) 3.0000 in

B) Back Flex (88.90 mm) 3.5000 in

Belt Strength:

Pull for 1% Elongation (22 N/mm) 125 lbs/sq in

Splice Instructions:

Foil	Yes
Splice Process	Finger
Press Temperature (°F)	356 °F
Press Pressure (psi)	29 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	Yes
FDA Approved	No

Special Characteristics:

#139COS is designed to handle light to medium duty conveying applications in distribution centers and airports.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO 800-727-2358 314-344-8500	Boise, ID 800-423-4469 208-342-4681	Charlotte, NC 800-849-2358 704-949-2100	Grand Prairie, TX 800-727-2358 314-344-8555	Philadelphia, PA 800-777-1314 215-295-1900	Sacramento, CA 800-289-2358 916-419-7191	Vancouver, WA 800-234-2358 360-567-4280	Beltservice Canada 877-210-7423 905-565-9217	Beltservice de Mexic +52 55 53620434 +44 2980 3266
--	--	--	--	---	---	--	---	---

NON WOVEN BELTS


PHSW 125 BLACK PVC C X B FR

139COS


Catalog Number

50567

Part Number



Top Cover View



Bottom Cover View



Ply View



BELTSERVICE
CORPORATION

beltservice.com

REV 3/23