

LIGHTWEIGHT THERMOPLASTICS SPECIFICATIONS

Catalog # 118BLTFR

Item number: 50258

Description:

2 Ply Black PVC Basket Weave Flame Retardant


International Designation:

E12/2 V0/V8 Black LT FR

Construction:

Compound Top Cover Black PVC Top Cover Thickness (in) (0.85 mm) 0.0335 in **Top Cover Description** Lattice Top Cover Shore 50 A Black PVC Compound Bottom Cover (0.00 mm) 0.0000 in Bottom Cover Thickness (in) **Bottom Cover Description Quiet Weave Bottom Cover Shore** N/A Number of Plies 2 Anti Static Yes Overall Gauge (in) (2.30 mm) 0.0906 in Unit Weight- lb/PIW 0.0410 lbs/PIW Material Between Plies **PVC** Maximum Width (in) 78 in Temperature Range (°F)- High 175 °F Temperature Range (°F)- Low 10 °F

Pulley Diameter, Minimum



A) Normal Flex

(30.48 mm) 1.2000 in

B) Back Flex

(50.80 mm) 2.0000 in

Belt Strength:

Pull for 1% Elongation

(12 N/mm) 68 lbs/sq in

Splice Instructions:

FoilNoSplice ProcessFingerPress Temperature (°F)345 °F

Press Pressure (psi) 19 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid Yes

Impression TopYesOil ResistantNoFire ResistantYesFDA ApprovedNo

Special Characteristics:

#118BLT-FR features a lattice top impression in the top cover which offers high friction characteristics for logistics applications.

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO Boise, ID Charlotte, NC Grand Prairie, TX Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-423-4469 800-234-2358 +52 55 53620434 800-727-2358 800-849-2358 800-727-2358 800-777-1314 800-289-2358 877-210-7423 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



National Industrial Belting Association

©Beltservice Corp.

PVC/NBR PROFILE/STICKY TOP COVERS

2 PLY BLACK PVC BASKET WEAVE FLAME RETARDANT INTERNATIONAL DESIGNATION: E12/2 VO/V8 BLACK LT FR



50258

Part Number





