

## **LIGHTWEIGHT THERMOPLASTICS SPECIFICATIONS**

Catalog # **112HCR** 

41735 Item number:

**Description:** 

2 Ply Poly HCR 69 Black PVC M AS

**International Designation:** 

E12/2 U0/V5 M AS

Construction:

Compound Top Cover Black PVC Top Cover Thickness (in) (0.50 mm) 0.0197 in

**Top Cover Description** Matte

Top Cover Shore 70

Polyester Compound Bottom Cover

Bottom Cover Thickness (in) (0.00 mm) 0.0000 in **Bottom Cover Description** PU Impregnated

**Bottom Cover Shore** N/A

Number of Plies 2


Anti Static Yes Overall Gauge (in) (2.70 mm) 0.1063 in

0.0512 lbs/PIW Unit Weight- lb/PIW

Material Between Plies **PVC** Maximum Width (in) 78 in

158 °F Temperature Range (°F)- High 14 °F Temperature Range (°F)- Low

### **Pulley Diameter, Minimum**



A) Normal Flex

(60.00 mm) 2.3622 in

B) Back Flex

(90.00 mm) 3.5433 in

### **Belt Strength:**

Pull for 1% Elongation

(12 N/mm) 69 lbs/sq in

#### **Splice Instructions:**

Foil Yes Splice Process Finger 320 °F Press Temperature (°F) Press Pressure (psi) 25 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

#### Other:

Cross Rigid Yes

Impression Top No Oil Resistant Yes Fire Resistant No

FDA Approved No

### **Special Characteristics:**

The 112HCR is a highly cross rigid monofilament carcass designed specifically for horizontal to incline or "Z" shaped conveying systems. The top cover is a 70A durometer and 0.5mm thick for standard conveying of lightweight parts or plastics, the carcass is a 12N/mm strength fabric for low stretch and antistatic properties. The PVC cover has limited oil and grease resistance, while offering excellent release with the matte finish surface.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*

Charlotte, NC Boise, ID Sacramento, CA St. Louis, MO Grand Prairie, TX Philadelphia, PA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 800-727-2358 208-342-4681 215-295-1900 +44 2980 3266 314-344-8500 704-949-2100 314-344-8555 916-419-7191 360-567-4280 905-565-9217



# **MATERIAL HANDLING PVC**

2 PLY POLY HCR 69 PIW BLACK PVC M AS INTERNATIONAL DESIGNATION: E12/2 U0/V5 M AS







