

**Catalog # 139B**
**Item number: 10867**
**Description:**


NW 40 Black HC

**International Designation:**

NW 40 HC SF Black

**Construction:**

Compound Top Cover	Polyester Fleece
Top Cover Thickness (in)	(0.00 mm) 0.0000 in
Top Cover Description	Non-Woven
Top Cover Shore	N/A
Compound Bottom Cover	Polyester Fleece
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Bottom Cover Description	Non-Woven
Bottom Cover Shore	N/A
Number of Plies	1
Anti Static	Yes
Overall Gauge (in)	(4.00 mm) 0.1574 in
Unit Weight- lb/PIW	0.0430 lbs/PIW
Material Between Plies	N/A
Maximum Width (in)	72 in
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	14 °F

**Pulley Diameter, Minimum**


A) Normal Flex (88.90 mm) 3.5000 in

B) Back Flex (88.90 mm) 3.5000 in

**Belt Strength:**

Pull for 1% Elongation (18 N/mm) 100 lbs/sq in

**Splice Instructions:**

Foil	No
Splice Process	Skive
Press Temperature (°F)	180 °F
Press Pressure (psi)	18 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

**Other:**

Cross Rigid	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

**Special Characteristics:**

This belt is designed for wear and cut resistance, soft impact surface, high temperature resistance up to 250° F, and is quiet running with the felt type construction. Most common industries using this belt are the automotive industry, mail and postal sorting, airports, package handling, packing lines and cutting machines.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*

<b>St. Louis, MO</b> 800-727-2358 314-344-8500	<b>Boise, ID</b> 800-423-4469 208-342-4681	<b>Charlotte, NC</b> 800-849-2358 704-949-2100	<b>Grand Prairie, TX</b> 800-727-2358 314-344-8555	<b>Philadelphia, PA</b> 800-777-1314 215-295-1900	<b>Sacramento, CA</b> 800-289-2358 916-419-7191	<b>Vancouver, WA</b> 800-234-2358 360-567-4280	<b>Beltservice Canada</b> 877-210-7423 905-565-9217	<b>Beltservice de Mexic</b> +52 55 53620434 +44 2980 3266
--	--	--	--	---	---	--	---	---

# NON WOVEN BELTS

NW 40 BLACK HC



INTERNATIONAL DESIGNATION: NW 40 HC SF BLACK

**139B**


Catalog Number

**10867**

Part Number



Top Cover View



Bottom Cover View



Ply View