

LIGHTWEIGHT THERMOPLASTICS SPECIFICATIONS

Catalog # 140FBS

Item number: 49904


Description:

NW 150 Black PVC F x F FR International Designation: ENW 26/1 V0/V0 Black FR

Construction:

Compound Top Cover **PVC Impregnated** Polyester Top Cover Thickness (in) (0.00 mm) 0.0000 in **Top Cover Description PVC Impregnated** Top Cover Shore Compound Bottom Cover **PVC** Impregnated Polyester Bottom Cover Thickness (in) (0.00 mm) 0.0000 in **Bottom Cover Description PVC Impregnated Bottom Cover Shore** N/A Number of Plies 1 Anti Static Yes (2.80 mm) 0.1102 in Overall Gauge (in) 0.0529 lbs/PIW Unit Weight- lb/PIW Material Between Plies N/A Maximum Width (in) 72 in Temperature Range (°F)- High 180 °F 0°F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(50.80 mm) 2.0000 in

B) Back Flex

(50.80 mm) 2.0000 in

Belt Strength:

Pull for 1% Elongation

(26 N/mm) 150 lbs/sq in

Splice Instructions:

Foil Yes
Splice Process Finger
Press Temperature (°F) 356 °F
Press Pressure (psi) 19 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid No

Impression Top No
Oil Resistant No
Fire Resistant Yes
FDA Approved No

Special Characteristics:

The 140FBS features a non-woven fabric that is ideal for package handling applications in distribution centers and airports. The PVC coated fabric is very durable, impact resistant, high tensile and flame retardant with excellent fastener holding capability.

*****All Values are nominal and subject to change without notice.*****

Grand Prairie, TX St. Louis, MO Boise, ID Charlotte, NC Philadelphia, PA Sacramento, CA **Beltservice Canada** Beltservice de Mexic Vancouver, WA 800-727-2358 800-423-4469 800-849-2358 800-727-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



National Industrial Belting Association

©Beltservice Corp.

NON WOVEN BELTS

NW 150 BLACK PVC F X F FR

INTERNATIONAL DESIGNATION: ENW 26/1 VO/VO BLACK FR





