

Catalog # **141Q**
Item number: **23427**
Description:


NW 120 Black PVC HM X F FR

International Designation:

NW 120 HM X F FR Black

Construction:

Compound Top Cover	Black PVC
Top Cover Thickness (in)	(0.89 mm) 0.0350 in
Top Cover Description	Matte
Top Cover Shore	N/A
Compound Bottom Cover	Polyester Fleece
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Bottom Cover Description	Friction Surface
Bottom Cover Shore	N/A
Number of Plies	1
Anti Static	No
Overall Gauge (in)	(2.54 mm) 0.1000 in
Unit Weight- lb/PIW	0.0500 lbs/PIW
Material Between Plies	N/A
Maximum Width (in)	72 in
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum


A) Normal Flex (63.50 mm) 2.5000 in

B) Back Flex (127.00 mm) 5.0000 in

Belt Strength:

Pull for 1% Elongation (12 N/mm) 69 lbs/sq in

Splice Instructions:

Foil	No
Splice Process	Skive
Press Temperature (°F)	180 °F
Press Pressure (psi)	18 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid	No
Impression Top	No
Oil Resistant	No
Fire Resistant	Yes
FDA Approved	No

Special Characteristics:

This belt is designed for Horizontal package handling, transport conveying, stackers, feeder and sorters. A low coefficient of friction allows a quiet running belt on slider beds, ideal for distribution centers and sort centers. Excellent for Pro Turn power turn applications in the package handling industry and airports. The needled woven polyester fabric construction is specially designed for fastener holding capability

*****All Values are nominal and subject to change without notice.*****

St. Louis, MO	Boise, ID	Charlotte, NC	Grand Prairie, TX	Philadelphia, PA	Sacramento, CA	Vancouver, WA	Beltservice Canada	Beltservice de Mexic
800-727-2358	800-423-4469	800-849-2358	800-727-2358	800-777-1314	800-289-2358	800-234-2358	877-210-7423	+52 55 53620434
314-344-8500	208-342-4681	704-949-2100	314-344-8555	215-295-1900	916-419-7191	360-567-4280	905-565-9217	+44 2980 3266

NON WOVEN BELTS

NW 120 HM X F FR



INTERNATIONAL DESIGNATION: NW 120 HM X F FR BLACK

141Q


Catalog Number

23427


Part Number



Top Cover View



Bottom Cover View



Ply View