



LIGHTWEIGHT THERMOPLASTICS SPECIFICATIONS

Catalog # 146

Item number: 10874

Description:

3 Ply Poly 171 White PVC C x C AS ATEX FDA


International Designation:

E30/3 P1/P2 White PVC C X C Smooth ATEX

Construction:

Compound Top Cover White PVC Top Cover Thickness (in) (2.00 mm) 0.0787 in **Top Cover Description** Smooth Top Cover Shore White PVC Compound Bottom Cover Bottom Cover Thickness (in) (1.00 mm) 0.0394 in **Bottom Cover Description** Smooth **Bottom Cover Shore** 73 Number of Plies 3 Anti Static Yes Overall Gauge (in) (6.10 mm) 0.2400 in 0.1317 lbs/PIW Unit Weight- lb/PIW Material Between Plies **PVC** Maximum Width (in) 78 in 176 °F Temperature Range (°F)- High 5°F Temperature Range (°F)- Low

Pulley Diameter, Minimum



A) Normal Flex

(200.00 mm) 7.8740 in

B) Back Flex

(250.00 mm) 9.8425 in

Belt Strength:

Pull for 1% Elongation

(30 N/mm) 171 lbs/sq in

Splice Instructions:

Foil Yes Splice Process Step Hot 347 °F Press Temperature (°F) Press Pressure (psi) 28 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid No

Impression Top No Oil Resistant Yes Fire Resistant Yes FDA Approved Yes

Special Characteristics:

The #146 belt is ideal for bucket elevators handling food products and recommended when high resistance to animal and vegetable oils and fats is needed. The antistatic polyester multifilament construction is suitable for troughed conveyors utilizing support rollers for maximum flexibility. ATEX compliant for use in potentially explosive environments.

*****All Values are nominal and subject to change without notice.*****

Boise, ID St. Louis, MO Charlotte, NC Grand Prairie, TX Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexic 800-727-2358 800-423-4469 800-849-2358 800-777-1314 800-289-2358 800-234-2358 877-210-7423 +52 55 53620434 800-727-2358 208-342-4681 215-295-1900 +44 2980 3266 314-344-8500 704-949-2100 314-344-8555 916-419-7191 360-567-4280 905-565-9217



NIBA National Industrial Belting Association

© Beltservice Corp.

PVC FDA

3 PLY POLY 171 WHITE PVC C X C AS ATEX FDA

INTERNATIONAL DESIGNATION: E30/3 P1/P2 WHITE PVC C X C SMOOTH ATEX

146
Catalog Number

10874
Part Number



Top Cover View Bottom Cover View Ply View

