

Catalog # 88LZ

Item number: 50261

**Description:** 

2 Ply 150 Black PVC Large Z x FS MOR

**International Designation:** 

N/A

**Pulley Diameter, Minimum** 

Minimum Pulley Diameter 8.00 in

**Belt Strength:** 

Tension Rating (PIW)

150 PIW

Construction:

Compound Top Cover PVC - MOR
Color Black

Top Cover Description Large - Z

Compound Bottom Cover Impregnated

Bottom Cover Description Friction Surface

Number of Plies 2

Overall Gauge (in) (9.53 mm) 3/8 in

Unit Weight- lb/PIW 0.1083 lbs/PIW

Carcass Type 2 Ply 150 Spun PET

Compound PVC - MOR

Temperature Range (°F)- High 180 °F

Temperature Range (°F)- Low -20 °F

**Splice Instructions:** 

Splice Step Yes
Splice Finger Yes

Other:

Static Conducting No
Cross Rigid No
High Heat No
Impression Top Yes
Oil Resistant Yes
Fire Resistant No
FDA Approved No

**Suggested Fasteners:** 

Flexco Plate/Rivet N/A
Flexco Hinged N/A
Alligator Staple N/A
Clipper Lace #1
Alligator Lace N/A

## **Special Characteristics:**

Incline belt used in agricultural applications as well as chemical, fertilizer, and other industrial applications. 2 ply construction for improved tracking vs. solid woven carcass. Deep impression for increased load capacities vs. standard Crescent and Chevron Top. Oil resistant PVC covers and profiles allow conveyance of materials such as shelled or un-shelled nut products. Continuous Z pattern allows for smooth and quiet running on return roller.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*

St. Louis, MO Boise, ID Charlotte, NC Grand Prairie, TX Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** 800-727-2358 800-849-2358 800-289-2358 800-234-2358 800-423-4469 800-727-2358 800-777-1314 877-210-7423 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217



Beltservice de Mexic

+52 55 53620434

+44 2980 3266

## **INCLINE SPECIALTY**

2 PLY 150 BLACK PVC LARGE Z X FS MOR



50261

**Part Number** 





