Catalog # 115A

Item number: 10754

**Description:** 


3 Ply Poly 85 Green PVC C x IP (USE UBR#200600)

International Designation: E15/3 V8IP/V7 Green NA

#### **Construction:**

Green PVC Compound Top Cover Top Cover Thickness (in) (0.70 mm) 0.0275 in **Top Cover Description** Smooth Top Cover Shore 80 Compound Bottom Cover Green PVC (0.80 mm) 0.0314 in Bottom Cover Thickness (in) Inverted Pyramid **Bottom Cover Description Bottom Cover Shore** 85 Number of Plies 3 Anti Static No Overall Gauge (in) (4.60 mm) 0.1811 in Unit Weight- lb/PIW 0.0833 lbs/PIW Material Between Plies **PVC** Maximum Width (in) 118 in 180 °F Temperature Range (°F)- High Temperature Range (°F)- Low 5°F

## **Pulley Diameter, Minimum**



A) Normal Flex

(99.82 mm) 3.9300 in

B) Back Flex

(139.95 mm) 5.5100 in

# **Belt Strength:**

Pull for 1% Elongation

(15 N/mm) 86 lbs/sq in

## **Splice Instructions:**

Foil Yes
Splice Process Finger
Press Temperature (°F) 330 °F
Press Pressure (psi) 25 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

### Other:

Cross Rigid No

Impression Top No
Oil Resistant No
Fire Resistant No
FDA Approved No

#### **Special Characteristics:**

The 115A belt is constructed of a high strength 3 ply monofilament carcass with a smooth 0.07 mm top PVC cover and an 0.08 mm thick inverted pyramid bottom cover. This belt is commonly used for hood wall belts in fiberglass insulation plants. The green PVC covers are ideal for most agricultural applications for transporting food products.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*

St. Louis, MO Boise, ID Charlotte, NC **Grand Prairie, TX** Philadelphia, PA Sacramento, CA Vancouver, WA **Beltservice Canada** Beltservice de Mexico 800-234-2358 800-727-2358 800-423-4469 800-849-2358 800-289-2358 877-210-7423 800-727-2358 800-777-1314 +52 55 53620434 314-344-8500 208-342-4681 704-949-2100 314-344-8555 215-295-1900 916-419-7191 360-567-4280 905-565-9217 +44 2980 3266



# **PVC/NBR PROFILE/STICKY TOP COVERS**

2 PLY POLY 57 GREEN PVC C X IP AS

INTERNATIONAL DESIGNATION: E10/2 V10IP/V10 GREEN AS



10776 **Part Number** 

