



WESTMINSTER

INTERNATIONAL LTD

Telephone : +44 (0)1295 756300

Fax : +44 (0)1295 756302

E-Mail : info@wi-ltd.com

Website : www.wi-ltd.com

WG Under Door Camera



The WG Under Door Camera is a black and white CCD camera built into a 6mm thick insertion plate for under door use; the system produces a full size video image on screen, and recording may be made onto the built in SD card DVR.

The camera control electronics are built into the plate, and the image is viewed on a large 5.6" monitor, the viewing direction is 15° forward, with a field of view of 70°, the 5.6" monitor supplies 12V to the camera plate via a single power/video cable.

SPECIFICATION

Camera Plate

- 400 TV lines
- 4-pin power/video cable to monitor
- Depth of field 250mm, infinity
- FOV 70°
- Image Sensor 1/4" B&W Resolution
- Sensitivity 0.005 Lux. DOV 15°
- Weight: 390gms



STANDARD FEATURES

- Clear, full screen video image
- Discreet briefcase housed
- Durable protective cover for monitor
- Large 5.6" screen
- Optional dual camera or built in IR versions available
- Optional pole attachment
- SD card video recording
- System in latest Peli-Storm case
- Up to 5 hours continuous use

SPECIFICATION

Monitor

- 5.6" LCD 640 x 480 resolution
- Batteries – Lithium Polymer up to 5 hours use
- CVBS (composite) / 1024x768 XVGA
- Dimensions 192 x 131 x 50mm
- LED back light
- BNC video connectors + CVBS and XVGA
- Operating temperature 0°C to 50°C Humidity 80%
- Power consumption 4 Watts approximately
- Power output for camera 12VDC / 500mA max
- Recording format -H.264 Resolution, PAL 704x576 NTSC 704x480 1500Kbps
- SD Card video recording 30fps maximum
- Weight 1kg

Case

- Peli-Storm
- Weight: 5 Kgs
- Dimensions: 508 x 373 x 147mm

OPTION

- An optional extra for the Under Door Camera is a 2 metre telescopic pole, which allows use of the camera from a safe area away from the door.